


District I 1625 N. French Dr., Hobbs, NM 88240
District II 1301 W. Grand Ave., Artesia, NM 88210
District III 1000 Rio Brazos Rd., Aztec, NM 87410
District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

WELL API NO. 30-045-33613
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No. E-3150-1



SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [] Gas Well [] Other []
2. Name of Operator Devon Energy Production Company L.P.
3. Address of Operator PO Box 6459, Navajo Dam, NM 87419
4. Well Location Unit Letter B : 1,300' feet from the North line and 1,340' feet from the East line
Section 16 Township 31N Range 7W NMPM County San Juan
11. Elevation (Show whether DR, RKB, RT, GR, etc.) GR 6,554'
Pit or Below-grade Tank Application [] or Closure []
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water
Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material

7. Lease Name or Unit Agreement Name Northeast Blanco Unit
8. Well Number 341
9. OGRID Number 6137
10. Pool name or Wildcat Blanco Mesaverde

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []

SUBSEQUENT REPORT OF:

- REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A []
CASING/CEMENT JOB [X]

OTHER: [] OTHER: []

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Drilled 12 1/4" hole to 300' on 4/19/06 set 9 jts of 9 5/8", H-40, ST&C, 32.3# casing at 292'. Cemented w/175 sx (37 bbls) "B" cement w/2% CaC1 and 1/4# PSX Floseal. Circulated 15 bbls of cement to surface. Test casing to 1500 psi.

Drilled 8 3/4" hole to 3,680' on 4/23/06, set 82 jts of 7", J-55 LT&C, 23# casing at 3,668'. Cemented lead w/550 sx (142 bbls) 50/50 POZ w/3% Gel, 5# Gilsonite, 1/4# Flocele, 1/10% CFR 3, 4/10% Halad 344 and tail w/75 sx (19 bbls) STD, 4/10% Halad 344. No cement to surface, top of cement is at 400'. Tested casing to 1500 psi.

Drilled 6 1/4" hole to 6,123' on 4/25/06, set 145 jts 4 1/2", J-55, LT&C, 11.6# casing at 6,114'. Cemented lead w/325 sx (88 bbls) 50/50 POZ w/2% Gel, 2/10% Veraset, 1/10% Diacel LWL. No cement to surface, top of cement is at 2,100'. Landed 2 3/8" production tubing at 5,928'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines [X], a general permit [] or an (attached) alternative OCD-approved plan [].

SIGNATURE [Signature] TITLE Senior Operations Technician DATE 5-30-06

Type or print name: Melisa Zimmerman E-mail address: Melisa.zimmerman@dvn.com Telephone No.: (405) 552-7917

For State Use Only

DEPUTY OIL & GAS INSPECTOR, DIST. 3

APPROVED BY: [Signature] TITLE DATE MAY 30 2006

Conditions of Approval (if any):

[Handwritten mark]