

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:		OIL WELL ☐	GAS WELL ☒	DRY ☐	Other ☐		
b. TYPE OF COMPLETION:		NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF. RESVR ☐	Other ☐
2. NAME OF OPERATOR BURLINGTON RESOURCES OIL & GAS COMPANY						5. LEASE DESIGNATION AND SERIAL NO. NMSF-077092	
3. ADDRESS AND TELEPHONE NO. PO Box 4289, Farmington, NM 87499 (505) 326-9700						6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface Unit P (SESE), 1000' FSL & 1050' FEL At top prod. interval reported below SAME At total depth SAME						7. UNIT AGREEMENT NAME	
14. PERMIT NO.						12. COUNTY OR PARISH San Juan	
DATE ISSUED						13. STATE New Mexico	
15. DATE SPUNDED 2/23/06		16. DATE T.D. REACHED 2/28/06		17. DATE COMPL. (Ready to prod.) 6/12/06		18. ELEVATIONS (DF, RKB, RT, BR, ETC.)* KB-5845'; GL-5834'	
20. TOTAL DEPTH, MD & TVD 2462'		21. PLUG BACK T.D., MD & TVD 2410'		22. IF MULTIPLE COMPL. HOW MANY*		23. INTERVALS DRILLED BY X	
24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* Basin Fruitland Coal 2104'- 2230'						25. WAS DIRECTIONAL SURVEY MADE NO	
26. LOGS GRICCL						27. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)							
CASING SIZE/GRADE		WEIGHT, LB./FT.		DEPTH SET (MD)		HOLE SIZE	
7"		20#, J55		132'		8 3/4"	
4 1/2"		10.5#, J55		2453'		6 1/4"	
29. LINER RECORD							
SIZE		TOP (MD)		BOTTOM (MD)		SACKS CEMENT*	
30. TUBING RECORD							
SIZE		DEPTH SET (MD)		PACKER SET (MD)			
2-3/8", 4.7# J-55		2230'		NONE			
31. PERFORATION RECORD (Interval, size and number)							
2 @SPF 2213'-2230'= 34 holes							
2 @SPF 2139'-2153'=14 holes							
2 @SPF 2104'-2117'=13 holes							
total holes= 88							
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.							
DEPTH INTERVAL (MD)				AMOUNT AND KIND OF MATERIAL USED			
2213'-2230'				2500 gal 25# x-link gel, 65000# 20/40 Brady sand, 110000			
				SCF N2, 75 quality N2, 90000# 20/40 Brady sand,			
				546 gal fluid and 16100 SCF N2, 14031000 SCF			
2104'-2153'				2000 gal 25# x-gel, 27000 gal 75 quality N2 foam, 25# linear			
				gel, 80000# 20/40 Brady sand, 608bbbls fluid, 1180000 SCF			
33. PRODUCTION							
DATE FIRST PRODUCTION SI		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Pump				WELL STATUS (Producing or shut-in) SI	
DATE OF TEST 6/12/06		HOURS TESTED 1 hr		CHOKE SIZE 2"		PROD'N FOR TEST PERIOD OIL-BBL 0	
FLOW. TUBING PRESS.		CASING PRESSURE SI - 116#		CALCULATED 24-HOUR RATE SI - 140#		GAS-MCF 8 mcf	
						WATER-BBL 0	
						OIL GRAVITY-API (CORR.)	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold							
35. LIST OF ATTACHMENTS This is a single FC.							
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records							
SIGNED Amanda Sanchez		TITLE Regulatory Analyst				DATE 6/13/06	

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

82

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries);					38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TOP	TRUE VERT. DEPTH
Ojo Alamo	1135'	1193'	White, cr-gr ss.	Ojo Alamo	1135'		
Kirtland	1193'	2045'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	1193'		
Fruitland	2045'	2245'	Dk gry-gr carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	2045'		
Pictured Cliffs	2245'		Bn-Gry, fine grn, tight ss.	Pic.Cliffs	2245'		