District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

## State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tan Type of action: Registration of a pit of	k covered by a "general plan"? Yes No or below-grade tank Closure of a pit or below-gr	o 🔀 ade tank 🗵
Operator: Dugan Production Corp Telephol Address: P.O. Box 420, Farmington, New Mexico 87401 Facility or well name: Dome Nav. 33-22-6 #2 API #:		
County: Sandoval Latitude 36.08937 Longitude 10		
Pit  Type: Drilling □ Production ☑ Disposal □  Workover □ Emergency □  Lined □ Unlined ☑  Liner type: Synthetic □ Thicknessmil Clay □  Pit Volume77 ±bbl	Below-grade tank  Volume:bbl Type of fluid:  Construction material:  Double-walled, with leak detection? Yes	
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	50 feet or more, but less than 100 feet 100 feet or more	(10 points)
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) ( 0 points)
	Ranking Score (Total Points)	0
If this is a pit closure: (1) attach a diagram of the facility showing the pit's your are burying in place) onsite  offsite  If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No  Attach soil sample results and a diagram of sample locations and excavation	. (3) Attach a general	description of remedial action taken including
Additional Comments:		
12' x 12' x 3'± deep unlined production pit, center located 42 feet South	n 56° West of wellhead.	and a state of the
Use Backhoe to dig into pit and sample.  Collect 4-point composite soil sample from sidewalls and single sample of	of nit center for laboratory testing	
See attached field sampling report and laboratory test reports.	of pit center for laboratory testing.	
I hereby certify that the information above is true and complete to the bes has been/will be constructed or closed according to NMOCD guideling Date:	nes 🔀, a general permit 🔲, or an (attached) alter	native OCD-approved plan .
Printed Name/Title <u>Jeff Blagg, Agent</u> Signature  Your certification and NMOCD approval of this application/closure does otherwise endanger public health or the environment. Nor does it relieve regulations.	not relieve the operator of liability should the conter the operator of its responsibility for compliance with	nts of the pit or tank contaminate ground water or n any other federal, state, or local laws and/or
Approval: EZPUTY O'A & GAS INSPECTOR, DIST. &	Signature Denny 70	Date 1 6 2006

30-043-20664	36.08937×	107.47840	
CLIENT: DUGAN	1 · · · · · · · · · · · · · · · · · · ·	NEERING, INC. OMFIELD, NM 8	7413 LOCATION NO:
FIELD REPORT	: PIT CLOSURE	VERIFICAT	ON PAGE No: of
QUAD/UNIT: N SEC: 33	v. 33-22-6 WELL#:  TWP: 22 N RNG: 6W PM: -  * 1650 FWL CONTR	NM CNTY: SN ST: N	ENVIDONMENTAL
	. <u>NA</u> FT. x <u>NA</u> FT.		
DISPOSAL FACILITY:	NA	REMEDIATION ME	THOD: CLOSE AS (S
	<del></del>		. S56W FROM WELLHEAD.
			ST SURFACE WATER:
NMOCD RANKING SCORE:	NMOCD TPH CLOSURE STD:	SOUU PPM	
SOIL AND EXCAVATION	ON DESCRIPTION:	OVM CAI	IB. READ. = <u>53.9</u> ppm IB. GAS = <u>100</u> ppm <u>RF = 0.52</u> 640 am/pm DATE: <u>5/18</u>
SOIL TYPE: SAND SILTY SA	ND/ SILT / SILTY CLAY / CLAY /		
	OHESIVE SLIGHTLY COHESIVE / CO	PHESIVE / HIGHLY COHESIVE	
	OILS): LOOSE FIRM / DENSE / VERY		ACTIC
	IC / SLIGHTLY PLASTIC / COHESIVE / 'S): SOFT / FIRM / STIFF / VERY STIFI		ASTIC
	DMOIST / WET / SATURATED / SUPE	R SATURATED	
DISCOLORATION/STAINING OBSERTING OF DETECTED: YES NO E	EXPLANATION		
SAMPLE TYPE: GRAB / COMPOSIT	E A OF DTO	x17 x3 + UNL	NED PIT. USE BACKHOE.
ADDITIONAL COMMENTS:		DIG INN PIT X	
	E1	ELD 418.1 CALCULATIONS	
SCALE SAMP. TI	<del></del>		N DILUTION READING CALC. (ppm)
		(3)	
O FT			
N PIT PERIME		N/44	PIT PROFILE
	1	DVM ADING	
	SAMPLE	FIELD HEADSPACE	
n'	TO 1 @ 2 @		
(9)	(4) 3 @	,	12-
	5 @	-A	
A (2)	A CCG 4Pt BL	0.0	
		<b>V</b>	
\ <u>(4)</u>	(D) LABS	SAMPLES	
	SAMPLE A	MALYSIS TIME	
	CPB T	1330	
	770	1,000	
P.D PIT DERBEGGION: 5 C - 57: C:			
P.D. = PIT DEPRESSION; B.G. = BELO T.H. = TEST HOLE; ~ = APPROX.; T.B. TRAVEL NOTES:	W GRADE: B = BELOW		



## EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / Dugan	Project #:	94034-010
Sample ID:	Dome Navajo 33-22-6 #2	Date Reported:	05-23-06
Laboratory Number:	37177	Date Sampled:	05-18-06
Chain of Custody No:	14650	Date Received:	05-19-06
Sample Matrix:	Soil	Date Extracted:	05-22-06
Preservative:	Cool	Date Analyzed:	05-22-06
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	0.3	0.1
Total Petroleum Hydrocarbons	0.3	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Pit Closures 4 - Point @ 6'.

Mister n Waeters Analyst Bleuli Wall
Review



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / Dugan	Project #:	94034-010
Sample ID:	Dome Navajo 33-22-6 #2	Date Reported:	05-22-06
Laboratory Number:	37177	Date Sampled:	05-18-06
Chain of Custody:	14650	Date Received:	05-19-06
Sample Matrix:	Soil	Date Analyzed:	05-22-06
Preservative:	Cool	Date Extracted:	05-22-06
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	15.8	1.8
Toluene	6.7	1.7
Ethylbenzene	9.3	1.5
p,m-Xylene	21.5	2.2
o-Xylene	1.3	1.0
Total BTEX	54.6	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	98.0 %
	1,4-difluorobenzene	98.0 %
	Bromochlorobenzene	98.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments: Pit Closures 4 - Point @ 6'.

Analyst Review



## Chloride

leul Walle

Client: Blagg / Dugan Project #: 94034-010 Sample ID: Dome Navajo 33-22-6 #2 Date Reported: 05-22-06 Lab ID#: 37177 Date Sampled: 05-18-06 Sample Matrix: Soil Date Received: 05-19-06 Preservative: Cool Date Analyzed: 05-23-06 Condition: Cool and Intact Chain of Custody: 14650

Parameter Concentration (mg/Kg)

Total Chloride 616

Reference: Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments: Pit Closures 4 - Point @ 6'.

Mistrem Walter (