District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Santa Fe, NM 87505

Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No 🗌 Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🔀				
Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: + Cat on L		Sec <u>32 T 31W R 11W</u>		
	Longitude	NAD: 1927 🔲 1983 🔲		
Surface Owner: Federal State Private Indian				
Pit Type: Drilling Production Disposal Workover Emergency Lined Unlined Liner type: Synthetic Thicknessmil Clay Pit Volumebbl	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes			
Doubt to around water (continued distance from bottom of with a consend	Less than 50 feet	(20 points)		
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)		
high water elevation of ground water.)	100 feet or more	(0 points)		
Wellhead protection area: (Less than 200 feet from a private domestic	Yes No	(20 points) (0 points)		
water source, or less than 1000 feet from all other water sources.)				
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)		
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)		
imgation canais, unches, and percinnal and epitemeral watercourses.)	1000 feet or more	(0 points)		
	Ranking Score (Total Points)			
If this is a pit closure: (1) Attach a diagram of the facility showing the pit	's relationship to other equipment and tanks. (2) Indica	ate disposal location: (check the onsite box if		
your are burying in place) onsite offsite If offsite, name of facility				
remediation start date and end date. (4) Groundwater encountered: No 🔲	•	n. and attach sample results.		
(5) Attach soil sample results and a diagram of sample locations and excava	tions.	19 20 21 20		
Additional Comments:		A (7.23)		
See Attached Documentation				
	(viii)	2005		
		TALE DAY		
		200. 200 G		
		ST 3 3		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit , or an (attached) alternative OCD-approved plan .				
Date:				
Approval: Printed Name/Title Approval: GAS INSPECTOR, ONST. (2)	Signature BL HM	DEC 1 9 2005		

	BLAG	G ENGINEERING,	INC.	LOCATION NO: BITTS		
CLIENT: BP	1	P.O. BOX 87, BLOOMFIELD, NM 87413		icus		
		505) 632-1199		COCR NO: 1046		
FIELD REPORT: PIT CLOSURE VERIFICATION PAGE No: of						
LOCATION: NAME:				DATE STARTED: 12-12-02 DATE FINISHED: 12-12-07		
QUAD/UNIT: M SEC:	37 TWP: 31N RNG	: 11W PM: NM CNTY: SJ	S ST: NM	_		
QTR/FOOTAGE: 990	5/990'W 5	BUISW CONTRACTOR: High Do	sert (Heber)	ENVIRONMENTAL SPECIALIST:		
EXCAVATION APP	PROX. <u>6</u> FT. x	<u>6</u> FT. x <u>5</u> FT.	DEEP. CUBIC	YARDAGE:		
DISPOSAL FACILITY:	MA VA	PO REMEDIATE		CLOSE AS (S DRMATION: MV		
FIELD NOTES & RE	EMARKS.	LEASE: 101 10 1	1 - 3 1 T			
DEPTH TO GROUNDWATER:		ATED APPROXIMATELY	NEAREST SURF	FROM WELLHEAD.		
NMOCD RANKING SCORE:		CLOSURE STD: 5000 PP				
SOIL AND EYOM	VATION DESCRIPT	ION:		D. = <u>[30.7</u> ppm		
SOIL AND LACAY	VATION DESCRIPT	1014.	OVM CALIB. GAS			
SOIL TYPE: SAND (SIL	TY SAND SILT / SILTY (CLAY / CLAY / GRAVEL / OTHE		(am/pm DATE: 12-12-UZ		
SOIL COLOR: + (1)	Du JAN					
COHESION (ALL OTHERS):(CONSISTENCY (NON COHE	NON COHESIVE SLIGHTLY	COHESIVE / COHESIVE / HIGHLY	COHESIVE			
		TIC / COHESIVE / MEDIUM PLASTIC /	HIGHLY PLASTIC			
DENSITY (COHESIVE CLAY				(2) 2550		
MOISTURE: DRY SLIGHTL DISCOLORATION/STAINING		TURATED / SUPER SATURATED		(CrozED)		
HC ODOR DETECTED: YES		PLANATION -				
SAMPLE TYPE: (GRAB)COI	ADDON'TE # OF DTO		1 11.11	O Parkling		
ADDITIONAL COMMENTS:	to Remove	Fit W Steel tank tank + SAMPle.	HIT FIRM	SANDSXNQ		
BOTTOM	bedrock @	8' BG.	781 794			
		FIELD 418.1 CALC	ULATIONS			
SCALE	MP. TIME SAMP. ID	LAB NO. WEIGHT (g)	mL FREON DII	LUTION READING CALC. (ppm)		
N PIT PERI	IMETER	0)/14		PIT PROFILE		
	TANK Foot _	OVM READING				
I	TANK PRINT	SAMPLE FIELD HEADSPACE				
- ('->/	11.10	1@ 8 0.0	<u> </u>			
1	TEST Hole	2 @ 3 @	-	-6 ->		
		4@		^		
AG TO	A To	5@	ATT	- A		
	we II		-	. 11		
			5'			
V			-	1 18		
		LADCAMPIEC		1 1		
		LAB SAMPLES SAMPLE ANALYSIS TIME		<u> </u>		
SAMPLE		(1) EM TAM 1155				
JAM.		POSED				
P.D. = PIT DEPRESSION; B.G.	= BELOW GRADE: B = BELOW		, SA	NDSTUNE		
T.H. = TEST HOLE; ~ = APPRO	X.; T.B. = TANK BOTTOM		<u> </u>			
TRAVEL NOTES: CALLOUT: 12-12-02 1100 AM ONSITE: 12-12-02 1145						



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 8'	Date Reported:	12-13-02
Laboratory Number:	24413	Date Sampled:	12-12-02
Chain of Custody No:	10467	Date Received:	12-12-02
Sample Matrix:	Soil	Date Extracted:	12-13-02
Preservative:	Cool	Date Analyzed:	12-13-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Heaton LS #3 - Dehy.

Analyst C. Qui

Misterin Waeters