

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT



FORM APPROVED
OMB No. 1004-0137
Expires March 31, 2007

APPLICATION FOR PERMIT TO DRILL OR DEEPEN

1a. Type of Work <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM18325	
1b. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name FARMINGTON, NM	
2. Name of Operator Black Hills Gas Resources, Inc.		7. If Unit or CA Agreement, Name and No. Many Canyons 29-04-26 12	
E-mail: lbenally@bhep.com		8. Lease Name and Well No.	
Contact: Lynn Benally		9. API Well No. 30-039-29986	
3a. Address P. O. Box 249 Bloomfield NM 87413	3b. Phone No. (include area code) 505-634-1111	10. Field and Pool, or Exploratory Chozama Mesa East of Pictured Cliffs	
4. Location of Well (Report location clearly and in accordance with any State Requirements.) At surface 660' FNL 1,910' FWL NE 1/4 NW 1/4 Lat: 36° 42' 05.9" Long: 107° 13' 32.6" At proposed production zone		11. Sec., T., R., M., or Blk. and Survey or Area Sec. 26 T 29N R 4W C	
14. Distance in miles and direction from nearest town or post office. * Well is approximately 52 miles east of Bloomfield, NM.		12. County or parish Rio Arriba	13. State New Mexico
15. Distance from proposed location to nearest property or lease line, ft. (Also nearest Drig, unit line, if any) Unit= n/a Lease= 660'	16. No. of acres in lease 320.00	17. Spacing Unit dedicated to this well 160 NW 1/4	
18. Distance from proposed location to nearest well, drilling, completed or applied for, on this lease, ft. Shalk 29- ± 1,784' 4 #014	19. Proposed depth 4,500' TVD	20. BLM/BIA Bond No. on file NMB000230	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 7,420' GR	22. Approximate date work will start * July 31, 2006	23. Estimated duration 45-60 days drig + completion	

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- | | |
|---|--|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification. |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the authorized officer. |

25. Signature <i>Kathy L. Schneebeck</i>	Name (Printed/Typed) Kathy L. Schneebeck, 303-820-4480	Date June 30, 2006
Title Permit Agent for Black Hills Gas Resources, Inc.		
Approved by (Signature) <i>June L. Lohr</i>	Name (Printed/Typed)	Date 8/15/06
Title Acting AFM Minerals		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

(continued on page 2)

This action is subject to technical and procedural review pursuant to 43 CFR 3165.3 and appeal pursuant to 43 CFR 3165.4

NMOC

DRILLING OPERATIONS AUTHORIZED ARE
SUBJECT TO COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS".

DISTRICT I
1625 N. French Dr., Hobbs, N.M. 88240

DISTRICT II
1301 W. Grand Ave., Artesia, N.M. 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, N.M. 87410

DISTRICT IV
1220 South St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised June 10, 2003

Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-039-29986	² Pool Code 74960	³ Pool Name Chozza Mesa Pictured Cliffs
⁴ Property Code 35952	⁵ Property Name MANY CANYONS 29-04-26	⁶ Well Number 12
⁷ OGRID No. 013925	⁸ Operator Name BLACK HILLS GAS RESOURCES	⁹ Elevation 7420


¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
C	26	29-N	4-W		660	NORTH	1910	WEST	RIO ARRIBA

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
¹² Dedicated Acres 160 acres - NW/4					¹³ Joint or Infill		¹⁴ Consolidation Code		¹⁵ Order No.

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



17 OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Kathy L. Schneebeck
Signature

Kathy L. Schneebeck
Printed Name

Permit Agent for Black Hills
Title

06/30/06
Date

18 SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

JUNE
Date

JOHN A. VIKOVICH
Signature of Registered Professional Surveyor


14831
Certificate No.

WELL PAD DIAGRAM

COMPANY: BLACK HILLS GAS RESOURCES
 LEASE: MANY CANYONS 29-04-26 No. 12
 FOOTAGE: 660 FNL 1910 FWL
 SEC.: 26 , TWN: 29-N , RNG: 3-W , NMPM
 ELEVATION: 7420'




SCALE IN FEET
 0 25 50



NOTE:

DAGGETT ENTERPRISES, INC. IS NOT LIABLE FOR UNDERGROUND UTILITIES OR PIPELINES. NEW MEXICO ONE CALL TO BE NOTIFIED 48 HOURS PRIOR TO EXCAVATION OR CONSTRUCTION.

REVISION:	DATE:	REVISED BY:
EDIT PER ON SITE	06/22/06	B.L.
CHANGE PAD SIZE	11/07/05	G.V.
 Daggett Enterprises, Inc. Surveying and Oil Field Services P. O. Box 15068 • Farmington, NM 87401 Phone (505) 326-1772 • Fax (505) 326-6019 NEW MEXICO L.S. 14831		
DRAWN BY: G.V.	CAOFILE: MN397PL8	
ROW#: MN397	DATE: 07/11/05	

WELL PAD CROSS-SECTIONAL DIAGRAM


COMPANY: BLACK HILLS GAS RESOURCES
 LEASE: MANY CANYONS 29-04-26 NO. 12
 FOOTAGE: 660 FNL, 1910 FWL
 SEC.: 26, TWN: 29-N, RNG: 4-W, NMPM
 ELEVATION: 7420'

NOTE:

DAGGETT ENTERPRISES, INC. IS NOT LIABLE FOR UNDERGROUND UTILITIES OR PIPELINES. NEW MEXICO ONE CALL TO BE NOTIFIED 48 HOURS PRIOR TO EXCAVATION OR CONSTRUCTION.

ELEV. A-A'

C/L




ELEV. B-B'

C/L



ELEV. C-C'

C/L



REF. DWG. MN397_PL8 WELL PAD DIAGRAM

REVISION:

DATE	11/07/06
REVISED BY	G.V.

Daggett Enterprises, Inc.
 Surveying and Oil Field Services
 P. O. Box 15068 • Farmington, NM 87401
 Phone (505) 326-1772 • Fax (505) 326-6019
 NEW MEXICO L.S. 14831



DRAWN BY: G.V.
 ROW#: MN397
 DATE: 07/11/05

Black Hills Gas Resources, Inc.
Many Canyons 29-04-26 12
660' FNL 1,910' FWL (NE/4 NW/4)
Sec. 26 T29N R4W
Rio Arriba County, New Mexico
Federal Lease: NMNM18325

DRILLING PROGRAM

This Application for Permit to Drill (APD) is filed under the Notice of Staking (NOS) process as stated in Onshore Order No. 1 and supporting Bureau of Land Management (BLM) documents. This NOS process included an on-site meeting on November 28, 2005, prior to the submittal of the application, at which time the specific concerns of Black Hills Gas Resources, Inc. (Black Hills) and the United States Forest Service – Jicarilla Ranger District (USFS) were discussed. USFS is the Surface Management Agency (SMA) for this wellpad and access road. All specific concerns of the USFS representatives are addressed herein, as are specific stipulations from the BLM.

This is a new vertical well to be drilled into the Pictured Cliffs formation. See also the attached Horizontal Drilling Program.

SURFACE FORMATION – San Jose

GROUND ELEVATION – 7,420'

ESTIMATED FORMATION TOPS - (Water, oil, gas and/or other mineral-bearing formations)

San Jose	Surface	Sandstone, shales & siltstones
Nacimiento	2,200'	Sandstone, shales & siltstones
Ojo Alamo	3,680'	Sandstone, shales & siltstones
Kirkland	3,825'	Sandstone, shales & siltstones
Fruitland Coal	4,000'	Sandstone, shales & siltstones
Pictured Cliffs	4,130'	Sandstone, shales & siltstones
Lewis	4,400'	Sandstone, shales & siltstones

TOTAL DEPTH 4,500' TVD

Estimated depths of anticipated fresh water, oil, or gas:

Tertiary

San Jose	surface	Gas
Nacimiento	2,200'	Gas
Ojo Alamo	3,680'	Gas
Fruitland Coal	4,000'	Gas
Pictured Cliffs	4,130'	Gas
Lewis	4,400'	Gas

HORIZONTAL DRILLING PROGRAM

CASING PROGRAM

Depth	Hole Diameter	Casing Diameter	Casing Weight and Grade	Cement
0' – 250' TVD	12-1/4"	8-5/8"	J-55 24# ST&C New	To surface (± 175 sxs Standard Cement containing 2% CaCl ₂ and 0.25 lb/sx LCM) **
0' – 4,500 TVD'	7-7/8"	5-1/2"	J-55 15.5# LT&C New	TD to surface (Lead: ± 300 sxs Lite Standard Cement. Tail: 400 sxs 50:50 POZ containing 0.25 lb/sx LCM)* **

* Actual cement volume to be determined by caliper log.

** Cement will be circulated to surface.

Yields:

Surface: Standard Cement yield: = 1.2 ft³/sx (mixed at 15.6 lb/gal)

Production: Lite Standard Cement yield: = 1.59 ft³/sx (mixed at 13.4 lb/gal)
50:50 POZ yield = 1.27 ft³/sx (mixed at 14.15 lb/gal)

All fresh water and prospectively valuable minerals encountered during drilling, will be recorded by depth and protected.

PRESSURE CONTROL

BOPs and choke manifold will be installed and pressure tested before drilling out under surface casing (subsequent pressure test will be performed whenever pressure seals are broken), and then will be checked daily as to mechanical operating condition. BOP's will be pressure tested at least once every 30 days. Ram type preventors and related pressure control equipment will be pressure tested to 1,000 psi. Annular type preventor will be pressure tested to 50% of the rated working pressure, not to exceed 1,000 psi. All casing strings will be pressure tested to 0.22 psi/ft. or 1,000 psi, whichever is greater, not to exceed 70% of internal yield.

BOP to be either double gate rams or an annular preventor as per Onshore Order No. 2.

Statement on Accumulator System and Location of Hydraulic Controls

The drilling rig has not yet been selected for this well. Selection will take place after approval of this application. Manual and/or hydraulic controls will be in compliance with Onshore Order No. 2 for 2M systems.

A remote accumulator will be used. Pressures, capacities, location of remote hydraulic and manual controls will be identified at the time of the BLM supervised BOP test.

MUD PROGRAM

0' - 300'	Fresh water – M.W. 8.5 ppg, Vis 30-33
300' - TD'	Clean Faze - Low solids non-dispersed M.W.: 8.5 – 9.2 ppg Vis.: 28 – 50 sec W.L.: 15cc or less

Sufficient mud materials to maintain mud properties, control lost circulation and to contain “kick” will be available at wellsite.

AUXILIARY EQUIPMENT

- A) A Kelly cock will be kept in the drill string at all times
- B) Inside BOP or stab-in valve (available on rig floor)
- C) Mud monitoring will be visually observed

LOGGING, CORING, TESTING PROGRAM

- A) Logging: DIL-CNL-FDC-GR – TD – BSC (GR to surface)
Sonic (BSC to TD)
- B) Coring: None
- C) Testing: Possible DST – None anticipated. Drill stem tests may be run on shows of interest

ABNORMAL CONDITIONS

- A) Pressures: No abnormal conditions are anticipated
Bottom hole pressure gradient – 0.31 psi/ft
- B) Temperatures: No abnormal conditions are anticipated
- C) H₂S: See H₂S Plan if H₂S is encountered.
- D) Estimated bottomhole pressure: 1,395 psi

ANTICIPATED START DATE

July 31, 2006


COMPLETION

The location pad will be of sufficient size to accommodate all completion activities and equipment. A string of 2-7/8” PH-6 tubing will be run for a flowing string. A Sundry Notice will be submitted with a revised completion program if warranted.

2-M SYSTEM

Black Hills Gas Resources, Inc.

ANNULAR PREVENTOR MAY BE SUBSTITUTED FOR DOUBLE GATE PREVENTORS
BOP PRESSURE TEST TO 1,000 PSI



Hydrogen Sulfide Drilling Operations Plan

I. Hydrogen Sulfide Training

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H_2S).
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H_2S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H_2S on metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H_2S Drilling Operations Plan and the Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H_2S zone (within 3 days or 500 feet) and weekly H_2S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H_2S Drilling Operations Plan and the Public Protection Plan. This plan shall be available at the well site. All personnel will be required to carry documentation that they have received the proper training.

II. H_2S Safety Equipment and Systems

Note: All H_2S safety equipment and systems, if necessary, will be installed, tested, and operational when drilling reaches a depth of 500 feet above or three days prior to penetrating the first zone containing or reasonably expected to contain H_2S .

A. Well control equipment:

1. Choke manifold with a minimum of one remote choke.
2. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit.

Black Hills Gas Resources, Inc.

- B. Protective equipment for essential personnel:
 - 1. Mark II Surviveair 30-minute units located in the doghouse and at briefing areas, as indicated on well site diagram.
- C. H₂S detection and monitoring equipment:
 - 1. Two portable H₂S monitors positioned on location for best coverage and response. These units have warning lights and audible sirens when H₂S levels of 10 ppm are reached.
- D. Visual warning systems:
 - 1. Wind direction indicators as shown on well site diagram.
 - 2. Caution/Danger signs shall be posted on roads providing direct access to location. Signs will be painted a high visibility yellow with black lettering of sufficient size to be readable at a reasonable distance from the immediate location. Bilingual signs will be used when appropriate. See example attached.
- E. Mud program:
 - 1. The mud program has been designed to minimize the volume of H₂S circulated to the surface. Proper mud weight, safe drilling practices, and the use of H₂S scavengers will minimize hazards when penetrating H₂S bearing zones.
- F. Metallurgy:
 - 1. All drill strings, casings, tubing, wellhead, blowout preventors, drilling spools, kill lines, choke manifold and lines, and valves shall be suitable for H₂S service.
 - 2. All elastomers used for packing and seals shall be H₂S trim.
- G. Communication:
 - 1. Cellular telephone communications in company vehicles.
- H. Well testing:
 - 1. Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity which are necessary to safely and adequately conduct the test. The drill stem testing will be conducted during daylight hours and formation fluids will not be flowed to the surface. All drill stem testing operations conducted in an H₂S environment will use the closed chamber method of testing.