

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2006 AUG 2 AM 11 47

1. **Type of Well**
GAS

2. **Name of Operator**
CONOCOPHILLIPS

3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**

Unit B (NWNE), 400' FNL & 2500' FEL, Sec. 8, T29N, R5W, NMPM

Lease Number
NMSF-078410
If Indian, All. or
Tribe Name

7. **Unit Agreement Name**

8. **San Juan 29-5 Unit
Well Name & Number**

9. **SJ 29-5 Unit #21C
API Well No.**

30-039-29553

10. **Field and Pool**

Blanco MV

11. **County and State**
Rio Arriba Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input checked="" type="checkbox"/> Change of Plans	<input checked="" type="checkbox"/> Other -
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction	
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging	<input type="checkbox"/> Non-Routine Fracturing	
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut off	
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection	

13. Describe Proposed or Completed Operations

Conocophillips requests permission to have the option to either drill a 12-1/4" hole for the surface casing, as permitted in our APDs or drilling a 13-1/2" hole. The new H&P rigs COPC is using have the capability of pumping the cement used at a higher rate than the older rigs. The larger hole makes it easier to run and cement of the surface casing.

Our drilling schedules change often and we don't know at the time of permitting which rig will be used to drill the well. This is the reason we need to have the option to use either size hole on the surface casing. The wells drilled with the H&P rigs will use the 13-1/2" hole & will use approx. 225 sx of Class G cement (1.17 yield @ 15.8 density). The cement will be pumped and circulated to surface.

14. I hereby certify that the foregoing is true and correct.

Signed Patsy Clugston Patsy Clugston Title Sr. Regulatory Specialist Date 7/31/06

(This space for Federal or State Office use)

APPROVED BY Pete Eng Title Pete Eng Date 8/4/06

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMOC