

Submit 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 88240
 District II
 1301 W. Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 March 4, 2004

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-045-29598
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name San Juan 31-6 Unit
8. Well Number #48F
9. OGRID Number 217817
10. Pool name or Wildcat Blanco MV / Basin DK
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6379' GL

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
 Oil Well Gas Well Other

2. Name of Operator
ConocoPhillips Company

3. Address of Operator
P.O. Box 4289, Farmington, NM 87499-4289

4. Well Location
 Unit Letter J : 1480 feet from the South line and 2125 feet from the East line
 Section 2 Township 30N Range R06W NMPM Rio Arriba County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input checked="" type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Conocophillips requests permission to have the option to either drill a 12-1/4" hole for the surface casing, as permitted in our APDs or drilling a 13-1/2" hole. The new H&P rigs COPC is using have the capability of pumping the cement used at a higher rate than the older rigs. The larger hole makes it easier to run and cement of the surface casing.

Our drilling schedules change often and we don't know at the time of permitting which rig will be used to drill the well. This is the reason we need to have the option to use either size hole on the surface casing. The wells drilled with the H&P rigs will use the 13-1/2" hole & will use approx. 225 sx of Class G cement (1.17 yield @ 15.8 density). The cement will be pumped and circulated to surface.

Plans are to also change the intermediate casing/cement design. A DV tool will be set at approx. 2700' and cemented per the attached wellbore diagram.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan.


SIGNATURE Patsy Clugston TITLE Sr. Regulatory Specialist DATE 8/15/06

Type or print name Patsy Clugston E-mail address: pclugston@br-inc.com Telephone No. 505-326-9518

(This space for State use)
 APPROVED BY [Signature] TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 35 DATE AUG 18 2006
 Conditions of approval, if any:

2

San Juan 31-6 # 48F
Schlumberger Cementing Program



SURFACE CASING :

Drill Bit Diameter	13.5"	
Casing Outside Diameter	9.625"	Casing Inside Diam. 9.001"
Casing Weight	32.3	ppf
Casing Grade	H-40	
Shoe Depth	235'	
Cement Yield	1.17	cuft/sk
Cement Density	15.8	lb/gal
Excess Cement	125	%
Cement Required	225	sx

SHOE 235 ', 9.625 ", 32.3 ppf, H-40 STC

INTERMEDIATE CASING :

Drill Bit Diameter	8.75"	
Casing Outside Diameter	7"	Casing Inside Diam. 6.456"
Casing Weight	20	ppf
Casing Grade	J-55	
Shoe Depth	3505'	
2nd Stage Cement Yield	2.63	cuft/sk
2nd Stage Cement Density	11.7	lb/gal
2nd Stage Cement Excess	150	%
2nd Stage Cement Required	268	sx
DV Tool Depth	2700'	
1st Stage Cement Length	805'	
1st Stage Cement Yield	1.28	cuft/sk
1st Stage Cement Density	13.5	lb/gal
1st Stage Cement Excess	150	%
1st Stage Cement Required	244	sx

DV Tool
@ 2700'

SHOE 3505 ', 7 ", 20 ppf, J-55 STC

PRODUCTION CASING :

Drill Bit Diameter	6.25"	
Casing Outside Diameter	4.5"	Casing Inside Diam. 4.000"
Casing Weight	11.6	ppf
Casing Grade	N-80	
Top of Cement	3305'	200' inside intermediate casing
Shoe Depth	7950'	
Cement Yield	1.44	cuft/sk
Cement Density	13	lb/gal
Cement Excess	50	%
Cement Required	491	sx

SHOE 7950 ', 4.5 ", 11.6 ppf, N-80 LTC