

Submit To, Appropriate District Office

State Lease - 6 copies

Fee Lease - 5 copies

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-105

Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.

30-039-26393

5. Indicate Type of Lease

STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:

OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐

b. Type of Completion:

NEW ☐ WORK ☐ PLUG ☐ DIFF. ☐ OTHER ☐
WELL ☐ OVER ☐ DEEPEN ☐ BACK ☐ RESVR. ☒

2. Name of Operator

McElvain Oil & Gas Properties, Inc.

3. Address of Operator

1050 17th Street, Suite 1800, Denver, CO 80265

4. Well Location

Unit Letter D : 1100 Feet From The North Line and 1100 Feet From The West LineSection 23 Township 26N Range 2W NMPM Rio Arriba County

10. Date Spudded

5/30/00

11. Date T.D. Reached

6/19/00

12. Date Compl. (Ready to Prod.)

8/15/01

13. Elevations (DF& RKB, RT, GR, etc.)

7496' GL

14. Elev. Casinghead

7496' GL

15. Total Depth

8508'

16. Plug Back T.D.

7093'

17. If Multiple Compl. How Many Zones?

NA

18. Intervals

Drilled By

Rotary Tools

All

Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name

Mesaverde 5678'-6080'

20. Was Directional Survey Made

Yes - attached

21. Type Electric and Other Logs Run

Induction, Neutron, Microlog, CBL

22. Was Well Cored

NA

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9-5/8"	36#	547'	12-1/4"	300 sx Class B	
5-1/2"	15.5# & 17#	8508'	8-3/4" & 7-7/8"	1278 sx - 3 stage	
DV tools @	3295' & 5902'				

24. LINER RECORD

SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN

25. TUBING RECORD

SIZE	DEPTH SET	PACKER SET
2-3/8"	7882'	

26. Perforation record (interval, size, and number)

5678'-5681' & 5689'-5696' - 2 spf 22 holes

6051'-6080' - 2 spf 58 sholes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.

DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED

5678-5696 Acidize w/500 gals 15% HCl, Frac w/20,000 gals

Foam w/20,000# 20/40 snd

6051-6080 Acidize w/1250 gals 15% HCl, Frac w/24,300 gals
2% KCl, 560,832 SCF N2, w/50,000# 20/40 snd

28. PRODUCTION

Date First Production

N/A

Production Method (Flowing, gas lift, pumping - Size and type pump)

Well Status (Prod. Or Shut-in)

SI

Date of Test

8/31/01

Hours Tested

8 hrs

Choke Size

Calculated 24-Hour Rate

Prod'n For Test Period

Oil - Bbl.

0

Oil - Bbl

0

Gas - MCF

0

Water - Bbl.

45

Gas - Oil Ratio

-

Flow Tubing Press.

0

Casing Pressure

260

Calculated 24-Hour Rate

0

Oil - Bbl.

0

Gas - MCF

0

Water - Bbl.

135

Oil Gravity - API - (Corr.)

-

29. Disposition of Gas (Sold, used for fuel, vented, etc.)

Test Witnessed By

Joe Elledge

30. List Attachments

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature

Printed

Name John D. Steuble

Title Engineering Manger

Date 9/25/01

100

his form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or reopened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

. Anhy	T. Canyon
. Salt	T. Strawn
. Salt	T. Atoka
. Yates	T. Miss
. 7 Rivers	T. Devonian
. Queen	T. Silurian
. Grayburg	T. Montoya
. San Andres	T. Simpson
. Glorieta	T. McKee
. Paddock	T. Ellenburger
. Blinebry	T. Gr. Wash
. Tubb	T. Delaware Sand
. Drinkard	T. Bone Springs
. Abo	T.
. Wolfcamp	T.
. Penn	T.
. Cisco (Bough C)	T.

Northwestern New Mexico

T. Ojo Alamo	3494'	T. Penn. "B"
T. Kirtland-Fruitland	3678'	T. Penn. "C"
T. Pictured Cliffs	3832'	T. Penn. "D"
T. Cliff House	5616'	T. Leadville
T. Menefee	5700'	T. Madison
T. Point Lookout	6034'	T. Elbert
T. Mancos	6174'	T. McCracken
T. Gallup		T. Ignacio Otzte
Base Greenhorn		T. Granite
T. Dakota	8056'	T.
T. Morrison		T.
T. Todilto		T.
T. Entrada		T.
T. Wingate		T.
T. Chinle		T.
T. Permian		T.
T. Penn "A"		T.

OIL OR GAS SANDS OR ZONES

o. 1, from.....to..... No. 3, from.....to.....
o. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

include data on rate of water inflow and elevation to which water rose in hole.

o. 1, from.....to.....feet.....

o. 2, from.....to.....feet.....

o. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology