Submit 3 Copies To Appropriate District Office District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	1220 South St. Fran Santa Fe, NM 87	DIVISION cis Dr. 5.	Form C-103 March 4, 2004 VELL API NO. 30-039-29598 Indicate Type of Lease STATE FEE State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well X Other			Lease Name or Unit Agreement Name San Juan 31-6 Unit Well Number #48F
2. Name of Operator			OGRID Number
ConocoPhillips Company			217817
3. Address of Operator P.O. Box 4289, Farmington, NM 87499-4289		I IC). Pool name or Wildcat Blanco MV/Basin Dakota
4. Well Location			Didico W V/Busin Bukou
T. Well Education			
Unit Letter <u>J</u> : 1480 feet from the <u>South</u> line and <u>2125</u> feet from the <u>East</u> line			
Section 2 Township 30N Range R6W NMPM Rio Arriba County			
11. Elevation (Show whether DR, RKB, RT, GR, etc.)			
NOTICE OF INT	propriate Box to Indicate Na ENTION TO: PLUG AND ABANDON CHANGE PLANS	SUBSE REMEDIAL WORK	QUENT REPORT OF: ALTERING CASING
TEMPORARILY ABANDON []	CHANGE PLANS []	COMMENCE DRILLII	ABANDONMENT
	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB	
OTHER		OTHER: Spud report	
 Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/10/06 PT casing to 1000#/30 min. RIH w/8-3/4". Tagged on cmt @ 193". D/O cmt and drilled ahead to 3510' 10/12/06. Circ hole. RIH w/82 jts, 7", 20#, J-55 ST&C & set @ 3466". Pre-flush 20 bbls gel ahead of Lead 368 sx (968 cf - 172 bbls slurry) D-079, D-046, CemNET. Tail 243 sx (311 cf - 55 bbls slurry) 50/50 POZ Class G, Bentonite, D-024, S-001, D-046, D-065. Dropped plug & displaced w/139 bbls FW. Bump plug to 1945#. Circ 90 bbls cmt to surface. WOC PT 7" casing to 1800#/30 min. 10/14/06 RIH w/ 6-1/4" Tagged on cmt @ 1800; D/O cmt & drilled ahead to 7951' TD 10/16/06. Circ hole. RIH w/ 192 jts, 4-1/2", 11.6#, N-80 LT&C casing & set @ 7941'. Pre-flush with 10/10/5 ahead of 499 sx (709 cf - 126 bbls slurry) 50/50 POZ Class G, CELLOPHANE, BENTONITE, D-024, D-167, D-065, D-800, D-046. Dropped Plug & displaced w/ 123 bbls FW. Bump plug to 2164#. RD and released rig 10/17/06. 			
PT casing and TOC will be reported on next report.			
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan.			
SIGNATURE Ohond Degles TITLE Regulatory Technician DATE 10/26/06			
Type or print name Rhonda Ro	ogers E-mail address: rog	errs@conocophillips.c	om Telephone No. 505-599-4018
(This space for State use)			
APPPROVED BY H. Villa	nuevaTITLE_	UTY OIL & GAS INSPEC	TOR, DIST. 65 DATE DATE