District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No

Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🔀					
Operator: BP America Production Company Telephone: (505)326-9200 e-mail address:					
Address: 200 Energy Ct, Farmington, NM 87401					
Facility or well name: RUSSEUL # 2 API#:	3004524050 U/Lor Otr/Otr M	Sec 24 TZ8N R 8 (4)			
County: San Juan Latitude					
Surface Owner: Federal State Private Indian	bongitude	1000 1027 (1000)			
	Relaw grade tonk				
Pit Type: Drilling Production Disposal	Below-grade tank Volume:bbl Type of fluid: Construction material: Double-walled, with leak detection? Yes				
Workover Emergency					
Lined Unlined					
Liner type: Synthetic Thicknessmil Clay _	Double-waited, with leak detection? Tes It not, explain why not.				
Pit Volumebbl					
THE VOICING	Less than 50 feet	(20 points)			
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)			
high water elevation of ground water.)	100 feet or more	(0 points)			
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)			
water source, or less than 1000 feet from all other water sources.)	No	(0 points)			
	Less than 200 feet	(20 points)			
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)			
tion canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(0 points)			
	Ranking Score (Total Points)				
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if					
your are burying in place) onsite 🔼 offsite 🔲 If offsite, name of facility_					
remediation start date and end date. (4) Groundwater encountered: No 🔀 Y	-	ft, and attach sample results.			
(5) Attach soil sample results and a diagram of sample locations and excavat	ions.				
Additional Comments:					
See Attached Documentation					
·					
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline	of my knowledge and belief. I further certify that the second of the sec	te above-described pit or below-grade tank			
and the construction of construction of the co					
Date: 11/01/2005					
Printed Name/Title Jeffrey C, Blagg, Agent Signature Juffy C. Slegy					
Your certification and NMOCD approval of this application/closure does not otherwise endanger public health or the environment. Nor does it relieve to regulations.	not relieve the operator of liability should the contents	of the pit or tank contaminate ground water or ny other federal, state, or local laws and/or			
roval: Printed Name/Title Printed Name/Title	Signature Branch Sell	Date: OCT 2 5 2006			

BLAGG ENGINEERING, INC. P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	LOCATION NO: 80830 C.O.C. NO: 8464			
FIELD REPORT: CLOSURE VERIFICATION	PAGE No: 1 of 1			
QUAD/UNIT: M SEC: 24 TWP: 28N RNG: 9W PM: NM CNTY: ST ST: NM	DATE STARTED: 1/15/01 DATE FINISHED: 1/16/01			
CTR/FOOTAGE: SW/4/SW/4 CONTRACTOR: FLINT	ENVIRONMENTAL JCB			
EXCAVATION APPROX. 20 FT. x 20 FT. x 3 FT. DEEP. CUBIC	YARDAGE: 44			
DISPOSAL FACILITY: ONSITE REMEDIATION METHO:				
LAND USE: RANGE LEASE: FED 29- 013860 A FOR				
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 120 FT. 1 DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000 NEAREST SURFACE	•			
NAMES THE COMPANY STR. 5000 DOM	CHECK ONE :			
SOIL AND EXCAVATION DESCRIPTION:	PIT ABANDONED STEEL TANK INSTALLED			
PIT EXCAUATED TO SANDSTONE BEDROCK				
0-3 COARSE GRAINED, YELLOW DRANGE, DRY, NON COHESINE S	EAND.			
@ 3' HIT FIRM BEDRUK SANDSTUNE.				
SAMPLE SAND @ TEX OF SAMPSTONE				
BEOROCK CLOSED FIELD 418.1 CALCULATIONS				
TIME SAMPLE I.D. LAB No: WEIGHT (g) mL. FREON DIL	LUTION READING CALC. ppm			
SCALE				
O FT OVM DIT	DDOFILE			
RESULTS FIT	PROFILE			
10 PIO (ppm) 1 N@ 3' 47.7				
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	0.5			
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	- 20 ·>			
9 3 20' AT				
3				
LAB SAMPLES SAMPLE AMAYOR THE	/ / / / / / / / EDPack			
To NG3' TPH 1015	ED ROCK ANDSTONE			
VIJEAD				
TDAUDI NOMBO				
TRAVEL NOTES: CALLOUT: ONSITE:				



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

		•	
Client:	Blagg / BP Amoco	Project #:	04034-010
Sample ID:	Dehy N @ 3'	Date Reported:	01-18-01
Laboratory Number:	19094	Date Sampled:	01-16-01
Chain of Custody No:	8464	Date Received:	01-16-01
Sample Matrix:	Soil	Date Extracted:	01-17-01
Preservative:	Cool	Date Analyzed:	01-18-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Limit (mg/Kg)
Gasoline Range (C5 - C10)	0.9	0.2
Diesel Range (C10 - C28)	6.1	0.1
Total Petroleum Hydrocarbons	7.0	0.1

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Russell #2.

Analyst L. Office

Mistine m Walten
Review