District | 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No 🗌

Type of action: Registration of a pit or below-grade tank 🔲 Closure of a pit or below-grade tank 🔀		
Operator: RP America Production Company Telephor	ne: (505)326-0200	
Operator: BP America Production Company Telephone: (505)326-9200 e-mail address:		
Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: RUSSEU # 2 API #:	3004524050 Hg = 00/00 M	sm 74 +78N pQ(1)
County: San Juan Latitude	Longitude	NAD: 1927 [1983]&
Surface Owner: Federal State Private Indian		
Pit	Below-grade tank	
Type: Drilling Production X Disposal	Volume:bbl Type of fluid:	· · · · · · · · · · · · · · · · · · ·
Workover Emergency	Construction material:	
Lined Unlined Thistoners will Clay T	Double-walled, with leak detection? Yes If not	, explain why not.
Liner type: Synthetic Thicknessmil Clay		
Pit Volumebbl	Leader 60 Gard	(20
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)
	100 feet or more	(0 points)
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)
water source, or less than 1000 feet from all other water sources.)	No	(0 points)
Division of a supervision of all supervision de places	Less than 200 feet	(20 points)
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)
tion canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(0 points)
	Ranking Score (Total Points)	
If this is a pit closure: (1) Attach a diagram of the facility showing the pit'	s relationship to other equipment and tanks. (2) Indian	
your are burying in place) onsite of offsite. If offsite, name of facility_		
remediation start date and end date. (4) Groundwater encountered: No		
	· · · · · · · · · · · · · · · · · · ·	T. and attach sample results.
(5) Attach soil sample results and a diagram of sample locations and excava	tions.	
Additional Comments:		
See Attached Documentation		
·		
I hereby certify that the information above is true and complete to the best	of my knowledge and balief. I further cortify that the	as above described his on below and so the
has been/will be constructed or closed according to NMOCD guideline	es 🔀, a general permit 🔲, or an (attached) alternal	tive OCD-approved plan .
		–
Date:		
Printed Name/Title Jeffrey C. Blagg, Agent Signature July C - Slegy		
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.		
roval: DEPUTY OIL & GAS INSPECTOR, DIST.	Signature BA BA	Date: OCT 2 5 2006



BLAGG ENGINEERING, INC. LOCATION NO. 80830 P.O. BOX 87, BLOOMFIELD, NM 87413 C.O.C. NO. 8464		
FIELD REPORT: CLOSURE VERIFICATION PAGE No: 1 of 1		
QUAD/UNIT: M SEC: 24 TWP: 28N RNG: 8W PM: NMCNTY: SJ ST: NM		
OTR/FOOTAGE: SW/4 SW/4 CONTRACTOR: FLINT SPECIALIST: JCB		
DISPOSAL FACILITY: NA REMEDIATION METHOD: NA LEASE: FED. 29-013860A FORMATION:		
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 75 FT. S60°E FROM WELLHEAD.		
DEPTH TO GROUNDWATER: >100 NEAREST VATER SOURCE: >1000 NEAREST SURFACE VATER: >1000 CHECK ONE: NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM SOIL AND EXCAVATION DESCRIPTION: STEEL TANK INSTALLED FIBERGLASS TANK INSTALLED EXCAVATED TEST Research		
EXCAVATED TEST PIT INTO CENTER OF PIT WITH BACKHOE. FOUND SILTY SAND, YELLOW ORANGE, MUIST, W/MINOR HC ODOR FROM PIT BOTTOM (Q4') TO TD Q 7' ENCOUNTERED VERY FIRM SANDSTONE BEDROCK Q7'. COLLECTED SOIL SAMPLE Q BEDROCK SURFACE.		
BEDROCK BETORION TIME SAMPLE I.D. LAB NO: WEIGHT (g) ML. FREON DILUTION READING CALC. ppm		
SCALE		
O FT OVM PIT PROFILE		
RESULTS SAMPLE PERD HEADSPACE PRO (ppm) 1 C@ 7 292 2 2 3 4 4 5 NELL HEAD A LAB SAMPLES SAMPLE PRO (ppm) 1 C@ 7 292 2 2 3 4 4 5 NELL HEAD A LAB SAMPLES SAMPLE ANALYSIS TIME C@ 7 TPH + 0900 SAMPSTONE BEDRUCK TRAVEL NOTES: CALLOUT: ONSITE:		



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP Amoco	Project #:	04034-010
Sample ID:	Separator C @ 7'	Date Reported:	01-18-01
Laboratory Number:	19091	Date Sampled:	01-15-01
Chain of Custody No:	8464	Date Received:	01-16-01
Sample Matrix:	Soil	Date Extracted:	01-17-01
Preservative:	Cool	Date Analyzed:	01-18-01
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	654	0.2
Diesel Range (C10 - C28)	277	0.1
Total Petroleum Hydrocarbons	931	0.1

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Russell #2.

Analyst Coleman

(Review Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP Amoco	Project #:	04034-010
Sample ID:	Separator C @ 7'	Date Reported:	01-18-01
Laboratory Number:	19091	Date Sampled:	01-15-01
Chain of Custody:	8464	Date Received:	01-16-01
Sample Matrix:	Soil	Date Analyzed:	01-18-01
Preservative:	Cool	Date Extracted:	01-17-01
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	1,920	1.8
Toluene	1,890	1.7
Ethylbenzene	791	1.5
p,m-Xylene	1,440	2.2
o-Xylene	1,840	1.0
Total BTEX	7,880	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Trifluorotoluene Bromofluorobenzene	100 % 100 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Russell #2.

Den L. Ofreca

Pristing Maeters
Review