

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-045-32660
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other	7. Lease Name or Unit Agreement Name: STATE GAS COM "N"
2. Name of Operator XTO Energy Inc.	8. Well Number #3
3. Address of Operator 2700 Farmington Ave., Bldg. K. Ste 1 Farmington, NM 87401	9. OGRID Number 5380
4. Well Location Unit Letter D : 720 feet from the NORTH line and 1190 feet from the WEST line Section 16 Township 31N Range 12W NMPM County SAN JUAN	10. Pool name or Wildcat BASIN FC / AZTEC PC
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 6155' GL	
Pit or Below-grade Tank Application ☐ or Closure ☐	
Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____	
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: **COMP SUMM** ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/28-11/15/06 MIRU. Un-hung rods. Unseated pmp. TOH & LD w/lmr, rod subs, rods, spiral rod guide, RHBO tl, pmp & stnr nip. BD & insp pmp on loc. Chkd OK. ND WH. NU BOP. PU & TIH w/tbg. TOH w/tbg, SN, OEMA w/1/4" weep hole & pin. TIH w/bit, csg scr, XO & tbg. EOT @ 2675'. TOH & LD w/tbg, XO, csg scr & bit. ND BOP. NU frac vlv. RDMO. MIRU WLU. RIH w/5-1/2" 10K CIBP & set @ 2560' (new PBTD). POH w/WL. MIRU acid equip. Perfd FC fr/2547' - 2313' (0.49" diam, ttl 78 holes). A. w/2000 gals 15% NEFE HCl acid. Balled off @ 3586 psg. RDMO ac equip. MIRU frac equip. Frac'd w/134,972 gals Delta 140 frac fld carrying 223,700# sd coated w/Sandwedge & Sandwedge NT. RDMO frac equip. MIRU pmp trk. Ppd dwn csg w/40 gals Methanol. RDMO pmp trk. MIRU. Ppd dwn csg w/20 bbls 2% KCl wtr & KW. ND frac vlv. NU BOP. <<<Con't on att>>>

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ , a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE *Lorri D. Bingham* TITLE REGULATORY COMPLIANCE TECH DATE 11/28/06
Type or print name **LORRI D. BINGHAM** E-mail address: regulatory@xtoenergy.com Telephone No. 505-324-1090

For State Use Only

APPROVED BY *H. Villanueva* TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 2 DATE NOV 30 2006
Conditions of Approval, if any:

8/12/14/06

Con't

PU & TIH w/NC, SN & tbg. MIRU AFU. RU pwr swivel. Estb circ w/AFU. CO fill fr/2510' – 2560' (CIBP). Circ 2 hrs. RD AFU. RD pwr swivel.

11/16/06 TOH & LD w/tbg. RU swb tls. BFL 2100' FS. S. 0 BO, 9 BLW, 8 runs, 1.5 hrs. FFL 2200' FS. Brn fld smpl w/no solids. FTP 0 psig. FCP 10-12 psig. RD swb tls. RU AFU. Estb circ w/AFU. CO fill fr/2549' – 2560' (CIBP). Circ 2 hrs. RD AFU. TOH w/tbg, SN & NC.

11/17/06 TIH w/OEMA w/1/4" weep hole & pin, SN & tbg. RIH w/ tbg broach to SN. POH w/tbg broach. LD tbg broach. Ld 2-3/8", 4.7#, J-55, EUE 8rd tbg w/donut & 2-3/8" seal assembly as follows: SN @ 2506'. EOT @ 2516'. TC perfs fr/2313' – 2547'. PBTD @ 2560' (CIBP). ND BOP. NU WH. RDMO.