

API NUMBER 30-045-08302

OPERATOR NAME Cross et al

WELL NUMBER #1

PROPERTY NAME Blackjack

SECTION 15 TOWNSHIP 29N

RANGE 13W

FOOTAGE 2843 FEL 2600 FWL

Sur Csg OD
OJO ALAMO 400-500' SUR CSG TD
Kirtland 500-800' SUR CSG WT
TOP OF CMT
ACTUAL
CACULATED
PROD CSG OD
PROD CSG TD
PROD CSG WT
TOP OF CMT
ACTUAL
CACULATED
PERF TOP
PERF BOTTOM
PACKER
TYPE OF PLUG
CIBP & CMT
CMT

XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX
XX	XX

PROPOSED PLUGGING OPERATION

TD @ 740' We have no record of the casing size, weight, or depth.

Do site prepration, dig out wellbore area. Determine casing size, Rig up well head

Install ancores, MIPU, install bop equipment, clean out well bore to TD 740 +-,
set bottom plug, test casing, fill well bore with cement from TD to surface.

NDBOP, cut off casing and install P&A Marker.

RDPU , cut off ancores,

Close pits according to guidelines: Clean and level location