

3-26-97

standind

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Burlington Resources Location: Unit B Sec. 16 Twp 30 Rng 8

Name of Well/Wells or Pipeline Serviced Standland Gas Comm 300

30-045-27064

Elevation _____ Completion Date 3-27-97 Total Depth 240' Land Type F

Casing Strings, Sizes, Types & Depths 8" PVC Sch 40, 20 ft.

If Casing Strings are cemented, show amounts & types used used 4 bags

Portland cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

none

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 130' hit Fresh water seep, 230' hit Fresh

water seep

Depths gas encountered: none

Ground bed depth with type & amount of coke breeze used: 240' depth

used 1200 lbs. Ioresco SU coke breeze

Depths anodes placed: 230', 206', 200', 194', 185'

Depths vent pipes placed: Surface to 240'

Vent pipe perforations: Bottom 100'

Remarks: _____

RECEIVED

MAR - 9 1999

OIL CON. DIV.

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

Contractors of Cathodic Protection Services

CP- GROUND BED CONSTRUCTION WORKSHEET

REMARKS (notes for construction log)

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #
100	1.0		295			490			685		
105	1.1		300			495			690		
110	1.9		305			500			695		
115	1.6		310			505			700		
120	.5		315	-		510			ANODE	DEPTH	NO COKE
125	.5		320			515			#		
130	.9		325			520			1	230	1.2
135	1.1		330			525			2	206	2.7
140	2.0		335			530			3	200	3.1
15	2.3		340			535			4	194	2.7
150	2.7		345			540			5	185	3.0
155	3.4		350			545			6		
160	3.4		355			550			7		
165	3.5		360			555			8		
170	3.3		365			560			9		
175	3.1		370			565			10		
180	3.4		375			570			11		
185	3.0	5	380			575			12		
190	2.6		385			580			13		
195	3.0	4	390			585			14		
200	3.3	3	395			590			15		
205	2.9	2	400			595			16		
210	2.0		405			600			17		
215	1.9		410			605			18		
220	1.7		415			610			19		
225	1.6		420			615			20		
230	1.2	1	425			620			21		
235	2.5		430			625			22		
240			435			630			23		
245			440			635			24		
250			445			640			25		
255			450			645			26		
260			455			650			27		
265			460			655			28		
270			465			660			29		
275			470			665			30		
280			475			670					
285			480			675					
290			485			680					