

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator BURLINGTON RESOURCES Location: Unit Q Sec. 36 Twp 30 Rng 11

Name of Well/Wells or Pipeline Serviced SEYOUR COM # 3 30-045-29509

Elevation _____ Completion Date 6-26-98 Total Depth 300 Land Type 5

Casing Strings, Sizes, Types & Depths _____

20' 8" PVC

If Casing Strings are cemented, show amounts & types used _____

NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used _____

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 80'-90' 3 GAL PER MIN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: _____

300' 1600^{lb} 5W LAROSCO

Depths anodes placed: 180-190-198-200-230-235-265-270

Depths vent pipes placed: 0-270

Vent pipe perforations: 170-270

Remarks: _____

RECEIVED
MAR - 9 1999

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

TIERRA DYNAMIC COMPANY			DEEP WELL GROUNDED LOG DATA SHEET						
COMPANY NAME: <u>BURLINGTON RESOURCES</u>			Ls E-2526-16						
WELL NAME: <u>SEVEN COM # 3</u>									
LEGAL LOCATION: <u>36-30-11</u>			COUNTY: <u>SAN JUAN NM</u>						
DATE: <u>6-26-98</u>			TYPE OF COKE: <u>SW</u>						
DEPTH: <u>300</u>			AMT. OF COKE BACKFILL: <u>1600</u>						
BIT SIZE: <u>6 1/8</u>			VENT PIPE: <u>0-770</u>						
DRILLER NAME: <u>MEACER</u>			PERF. PIPE: <u>170-270</u>						
SIZE AND TYPE OF CASING: <u>20' 8" PVC</u>			ANODE AMT. & TYPE: <u>8</u>						
			BOULDER DRILLING:						
DEPTH			DEPTH			COMPLETION INFORMATION:			
FT.	LOG	ANODE	FT.	LOG	ANODE	FT.	LOG	ANODE	WATER DEPTHS: <u>80'-90'</u>
									ISOLATION PLUGS:
100	1.5		265	1.9		430			
105	1.3		270	2.2		435			OUTPUT OUTPUT
110	1.3		275	1.9		440			ANODE# DEPTH NO COK COKED
115	1.4		280	1.7		445			1 270 2.1 8.0
120	1.4		285	1.3		450			2 265 2.1 7.9
125	1.2		290	1.7		455			3 235 2.1 2.9
130	.7		295	1.7		460			4 230 1.9 8.2
135	1.6		300			465			5 200 2.0 8.3
140	2.4		305			470			6 195 2.0 7.5
145	2.0		310			475			7 190 2.0 7.6
150	1.9		315			480			8 180 2.0 7.2
155	1.8		320			485			9
160	1.7		325			490			10
165	1.9		330			495			11
170	1.9		335			500			12
175	2.1		340			505			13
180	1.7		345			510			14
185	2.1		350			515			15
190	2.0		355			520			16
195	2.1		360			525			17
200	2.0		365			530			18
205	2.0		370			535			19
210	1.9		375			540			20
215	1.6		380			545			21
220	2.0		385			550			22
225	2.0		390			555			23
230	2.1		395			560			24
235	2.1		400			565			25
240	1.3		405			570			26
245	1.2		410			575			27
250	1.8		415			580			28
255	1.8		420			585			29
260	1.9		425			590			30
						595			
LOGGING VOLTS: <u>11.5</u>			VOLTAGE SOURCE: <u>BAT</u>						
TOTAL AMPS: <u>23.5</u>			TOTAL G/B RESISTANCE: <u>0.493</u>						
REMARKS:									