

3709

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

30-045-07265

Operator Meridian Oil Inc. Location: Unit Q Sec. 21 Twp 28 Rng 10

Name of Well/Wells or Pipeline Serviced _____

KUTZ Deep Test #1

Elevation 6124' Completion Date 8/26/93 Total Depth 429' Land Type F

Casing Strings, Sizes, Types & Depths 7/6 Set 59' of 8" PVC CASING.

NO GAS, WATER, or Boulders were ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 12 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 110', AND MORE AT

325'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 429' DEPTH.

Used 120 SACKS OF Asbury 218R (6000#)

Depths anodes placed: 413', 405', 319', 288', 281', 274', 267', 260', 253', 246', 239', 232', 196', 188', +180'

Depths vent pipes placed: SURFACE TO 429'.

Vent pipe perforations: BOTTOM 320'.

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.