

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS

NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

3275

Rincon Unit Wells
 #128 30-039-06886
 #197 30-039-20657
 #62 30-039-06664

#25 30-039-24657

Operator: UNOCAL - Bloomfield, NM Location: Unit L Sec. 28 Twp. 27N Rng. 7W

Name of Well/Wells or Pipeline Served: RINCON UNIT WELLS: 128 DK; 197 PC; 62 PC; 251 FC

Elevation: 6679 GL Completion Date: 10/16/95 Total Depth: 340' Land Type* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible:

WET SANDSTONE AT 180'

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 2500 LBS., SWB METALURGICAL PETROLEUM COKE

Depths anodes placed: 190' 200' 210' 220' 230' 260' 270' 300' 310' 320

Depths vent pipes placed: 0' - 340', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 300'

Remarks: SECOND GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee
 If Federal or Indian, add Lease Number.

RECEIVED
 FEB - 5 1996

OIL CON. DIV.
 DIST. 3



NET. 210' - WELL #128



RINCON UNIT 128
" " 197
" " 62

DWG. NO. 00027-07 REV.

NO

REVISION

DATE _____

COMPANY: Unocal DATE: 10-16-85
 WELL: Rincon #128; 19.7; 251; 62 PIPELINE:
 LOCATION: 1A 1A SEC. 28-27-7 STATE: N.M.
 GROUND BED: DEPTH: 340 DIAMETER: 6 3/4" BACKFILL: Metallurgical ANODES TYPE: Dunichler 51

DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		Logged	Coked	R		
20	Sand Stone					
30	Sand Stone					
40	Sand Stone					
50	Sand Stone					
60	Sand Stone					
70	Sand Stone					
80	Sandy Shale					
90	Sandy Shale					
100	Sandy Shale					
110	Shale					
120	Shale					
130	Shale					
140	Shale					
150	Shale					
160	Shale					
170	Sand Stone					
180	Sand Stone					Wet sand stone
190	Sandy Shale	1.1	2.6		190'	
200	Sandy Shale	1.6	2.9		200'	
210	Shale	2.1	3.7		210'	
220	Shale	1.3	2.7		220'	
230	Shale	1.3	2.1		230'	
240	Sand Stone	2				
250	Sand Stone	1				
260	Sandy Shale	7	1.0		260'	
270	Sandy Shale	1.0	1.6		270'	
280	Sand Stone	1				
290	Sand Stone	1				
300	Sandy Shale	4	7		300'	
310	Sandy Shale	4	8		310'	
320	Sandy Shale	6	1.8		320'	
330	Sand Stone	3				
340	Sand Stone	2				
350						

NOTES:

POWER SOURCE: Battery VOLTS: 8.5
 INDICATE WATER ZONE DEPTHS Wet sand stone 180'
 CASING RUN: YES / ☒ NO TYPE: _____ DEPTH: _____ CEMENTED: YES / ☒ NO
 ISOLATION PLUGS SET: YES / ☒ NO IF SO, WHERE: _____
 TOTAL: AMPS 7.5 RESISTANCE: 1.133

CON UNIT

