

3248

OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO

#9 → 30-039-07476

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFI

#107 → 30-039-20453

OPERATOR: PHILLIPS PETROLEUM CO.
FARMINGTON, NM 87401
PHONE: 599-3400

RECEIVED
FEB 10 1998
OIL CON. DIV.
DIST. 3

LOCATION INFORMATION

WELLNAME OR PIPELINE SERVED: SJ 29-6 UNIT #9 MV

ADDITIONAL WELLS: SJ 29-6 #107

LEGAL LOCATION M 36 29 6

DATE OF INSTALLATION: 4/15/97

LEASE NUMBER: 650112

TYPE OF LEASE: STATE

PPCO RECTIFIER NUMBER: FM-173

TOTAL G/B DEPT 420

GROUND BED INFORMATION

CASING SIZE: 8

CASING TYPE: PVC

CASING DEPTH: 20

CASING CEMENT: YES

TOP ANODE: 240

BOTTOM ANODE 386

INDIVIDUAL ANODE DEPTHS 240,274,281,288,295,302,309,316,350,356,362,368,374,380,386

AMOUNT OF COKE: 2700

WATER INFORMATION

WATER DEPTH (1): 140

WATER DEPTH (2):

CEMENT PLUGS: NO

OTHER INFORMATION

GAS DEPTH: NA

VENT PIPE DEPTH 397

TOP OF VENT PERFORATIONS: 197

REMARKS: NEW G/B DRILLED 4/15/97

IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE. UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

*- LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE

IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

CPS GROUND BED CONSTRUCTION WORKSHEET

27 like

SPR	P/L NAME () NUMBER ()		5529-6 #9		5529-6 #107	
JO	TOTAL	VOLTS (11.4)	AMPS (15.9)	= CHMS (.7)	DATE (4-15-97)	NAME (Jack Ledbetter)

REMARKS (notes for construction log)

Drill 11" hole 20' and set 20' of 8" PVC casing and cement to surface

(4 Bags Portland) Drill from 20' - 420' and set 15 anodes and 2700 lbs

16 res to SW coke breeze. 420' of vent pipe with bottom 200' vented

Pour cement and tie off wires, (H_2O at 140' 2 gpm)

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #
100			295	1.9	17	490			685		
105			300	2.2	10	495			690		
110			305	1.5		500			695		
115			310	1.4	9	505			700		
120			315	1.2	8	510			ANODE	DEPTH	NC
125			320	.6		515			#		COKE
130			325	.7		520			1	386	1.7
135			330	.7		525			2	380	1.3
140			335	.5		530			3	374	1.5
15			340	.4		535			4	368	1.6
150	0.9		345	.2		540			5	362	2.2
155	.5		350	1.1	7	545			6	356	2.1
160	2.5		355	2.2	6	550			7	350	1.2
165	.7		360	2.4	5	555			8	346	1.0
170	.4		365	1.7		560			9	309	1.3
175	.6		370	1.5	4	565			10	302	2.0
180	.6		375	1.3	3	570			11	295	1.6
185	1.2		380	1.8	2	575			12	288	1.7
190	1.3		385	1.9		580			13	281	1.4
195	1.7		390	1.8	#1	585			14	274	1.1
200	.7		395	3.97	TB	590			15	246	1.1
205	.6		400			595			16		
210	.5		405			600			17		
215	.4		410			605			18		
220	.4		415			610			19		
225	.4		420			615			20		
230	.4		425			620			21		
235	.6		430			625			22		
240	1.2	15	435			630			23		
245	.7		440			635			24		
250	.7		445			640			25		
255	.5		450			645			26		
260	.7		455			650			27		
265	.6		460			655			28		
270	.3		465			660			29		
275	1.2	14	470			665			30		
280	.5	13	475			670					
285	1.7		480			675					
290	.7		485			680					