

3253

**OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFI

OPERATOR: PHILLIPS PETROLEUM CO.
FARMINGTON, NM 87401
PHONE: 599-3400

30-039-25669

RECEIVED
FEB 10 1998
OIL CON. DIV.
DIST. 3

LOCATION INFORMATION

WELLNAME OR PIPELINE SERVED: SJ 30-5 #27-M

ADDITIONAL WELLS: NA

LEGAL LOCATION C-20-30-5

DATE OF INSTALLATION: 7/8/97

LEASE NUMBER: SF-078740

TYPE OF LEASE: FEDERAL

PPCO RECTIFIER NUMBER: FM-610

TOTAL G/B DEPT 320

GROUND BED INFORMATION

CASING SIZE: 8

CASING TYPE: PVC

CASING DEPTH: 20

CASING CEMENT: YES

TOP ANODE: 200

BOTTOM ANODE 285

INDIVIDUAL ANODE DEPTHS 200,210,220,230,240,250,259,265,275,285

AMOUNT OF COKE: 2200

WATER INFORMATION

WATER DEPTH (1): 120

WATER DEPTH (2): NA

CEMENT PLUGS: NA

OTHER INFORMATION

GAS DEPTH: NA

VENT PIPE DEPTH 320

TOP OF VENT PERFORATIONS: 200

REMARKS: G/B DRILLED 7-97

IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE. UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

*- LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE

IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

PPCO.GROUNDBED LOG

PHILLIPS PETROLEUM CO.			DEEP WELL CATHODIC PROTECTION GROUNDBED LOG-DATA SHEET					
DRILLED BY: (DRILLER'S NAME AND COMPANY) JACK L. DUBETTER - TIERRA DYNAMIC CO.								
LOCATION NAME: 53.30-5#27M			DATE DRILLED: 7-8-97					
LEGAL LOCATION: Sec 20-30N-5W			SIZE AND TYPE OF CASING: 8" PVC					
PPCO ID NO. (FM NO.) 610			DEPTH OF CASING: 20'					
TOTAL DEPTH: 320'			COKE: (CIRCLE) PETR OR MET. AMOUNT: 2200 LBS.					
DIAMETER OF HOLE: 1 3/4			TYPE OF ANODES: Anodic Division					
COUNTY: R.D. Arriba								
COMPLETION INFORMATION:								
DEPTH FT.	LOG	ANODE	DEPTH FT.	LOG	ANODE	DEPTH FT.	LOG	ANODE
100			265	1.8	3	430		
105			270	1.8		435		
110			275	2.0	2	440		
115			280	2.0		445		
120			285	1.6	1	450		
125			290	1.1		455		
130			295	1.0		460		
135			300	.8		465		
140			305	.8		470		
145			310	.7		475		
150	1.1		315	T.D.		480		
155	1.0		320			485		
160	1.0		325			490		
165	1.6		330			495		
170	1.8		335			500		
175	1.7		340			505		
180	1.5		345			510		
185	1.3		350			515		
190	1.2		355			520		
195	1.2		360			525		
200	1.8	10	365			530		
205	2.0		370			535		
210	1.5	9	375			540		
215	1.1		380			545		
220	1.4	8	385			550		
225	1.8		390			555		
230	1.5	7	395			560		
235	1.4		400			565		
240	1.3	6	405			570		
245	1.6		410			575		
250	1.6	5	415			580		
255	1.1		420			585		
260	1.5	4	425			590		

LOGGING VOLTS: 11.44

VOLTAGE SOURCE: Auto

TOTAL AMPS: 14.2

TOTAL G/B RESISTANCE: .80

REMARKS: