

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Burlington Resources Location: Unit E Sec. 29 Twp 28 Rng 6

Name of Well/Wells or Pipeline Serviced San Juan 28-6 #147M

Elevation _____ Completion Date 7-20-97 Total Depth 295' Land Type _____

Casing Strings, Sizes, Types & Depths 20' 8" PVC Casing

If Casing Strings are cemented, show amounts & types used yes - 4 Bags

If Cement or Bentonite Plugs have been placed, show depths & amounts used
None

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. 190' Fresh

Depths gas encountered: None

Ground bed depth with type & amount of coke breeze used: 295' 2000/lbs
Lorexo Sw Coke Breeze

Depths anodes placed: 1-282', 276', 270', 264', 258', 252', 246', 237', 231', 225', 206', 200'

Depths vent pipes placed: Surface to 295'

Vent pipe perforations: Bottom to 206'

Remarks: _____

RECEIVED

FEB 25 1998

OIL COIN. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

ENTERED

CPS GROUND BED CONSTRUCTION WORKSHEET

20 Coke

9044-U P.I. NAME (), NUMBER () Burlington Resources S.S. 28-6 #147M

REMARKS (notes for construction log)

Drill 11" hole 20' and set 20' of 8" casing and cement (4 Bags)

Drill 8" hole from 20' - 300' and set 12 anodes and 2000 lbs

loresco su coke birze

Water At 190' 100

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #
100	2.0		295	2.95 TD		490			685		
105	1.7		300			495			690		
110	1.4		305			500			695		
115	1.3		310			505			700		
120	1.2		315			510			ANODE DEPTH NO COKE	FULL COKE	
125	1.0		320			515			#		
130	1.9		325			520			1	282	1.5
135	2.7		330			525			2	276	2.4
140	2.5		335			530			3	270	1.4
15	2.0		340			535			4	264	1.3
150	2.3		345			540			5	258	1.4
155	1.1		350			545			6	252	1.5
160	1.7		355			550			7	246	1.4
165	1.4		360			555			8	237	1.5
170	1.3		365			560			9	231	1.6
175	1.2		370			565			10	225	1.8
180	1.2		375			570			11	206	1.8
185	1.3		380			575			12	200	1.5
190	1.5		385			580			13		
195	1.5		390			585			14		
200	1.5	12	395			590			15		
205	1.8	11	400			595			16		
210	1.4		405			600			17		
215	1.8		410			605			18		
220	1.6		415			610			19		
225	1.8	10	420			615			20		
230	1.6	9	425			620			21		
235	1.5	8	430			625			22		
240	1.7		435			630			23		
245	1.4		440			635			24		
250	1.4	7	445			640			25		
255	1.0	6	450			645			26		
260	1.4	5	455			650			27		
265	1.3	4	460			655			28		
270	1.4	3	465			660			29		
275	2.3	2	470			665			30		
280	2.0	1	475			670					
285	1.7		480			675					
290	1.6		485			680					