District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

February 16, 2007

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes No

Type of action: Registration of a pit of	or below-grade tank L Closure of a pit or below-grade	le tank 🔀			
Operator: Burlington Resources Telephone:	(505) 326-9841 e-mail address: Lot	uis.E.Hasely@conocophillips.com			
Address: 3401 East 30th Street, Farmington, New Mexico, 87402	(505) 520-5641 C-man address. Lon	ns. E. rrasery@conocopiumps.com			
i	3004520740 U/L or Qtr/Qtr I	O Sec 34 T_26N_R 10W			
		_			
1	36.449687 Longitude -107.88938	NAD: 1927 ☑ 1983 ☐			
Surface Owner: Federal 🖾 State 🗌 Private 🗍 Indian 🗍		RCVD APR19'07			
<u>Pit</u>	Below-grade tank	OIL.CONS. DIV.			
Type: Drilling Production Disposal	Volume: 60 bbl Type of fluid: Produced Water and Incidental Off.				
Workover ☐ Emergency ☐	Construction material: Fiberglass DIST. 3				
	ed 🗌 Unlined 🗎 Double-walled, with leak detection? Yes 🔲 If not, explain why not.				
Liner type: Synthetic Thicknessmil Clay	No. Tank in place prior to Rule 50.				
Pit Volumebbl					
Depth to ground water (vertical distance from bottom of pit to seasonal	Less than 50 feet	(20 points)			
high water elevation of ground water.)	50 feet or more, but less than 100 feet	(10 points)			
ingli water organism or ground water.)	100 feet or more	(0 points) 0			
	Yes	(20 points)			
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points) 0			
water source, or less than 1000 feet from all other water sources.)		(o points)			
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)			
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)			
Ingation calada, diceitos, and percinial and optomeda watercourses.)	1000 feet or more	(0 points) 0			
	Ranking Score (Total Points)	0			
If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if you					
are burying in place) onsite \square offsite \square If offsite, name of facility (
(4) Groundwater encountered: No 🛛 Yes 🔲 If yes, show depth below gro	und surface ft. and attach sample result	s.			
(5) Attach soil sample results and a diagram of sample locations and excaval	ions.				
Additional Comments:					
The soils tested clean and no soil remediation was required.					
	Complementation and half of Theorem and the Abertain				
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline	of my knowledge and belief. If further certify that the \square , a general permit \square , or an (attached) alternat	ie above-described pit or below-grade tank ive OCD-approved plan .			
Date: 3/30/07					
Date: 77 57 7	5) Hash				
Printed Name/ I title Mr. Ed Hasely, Environmental Advisor Signature					
Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.					
•					
Printed Name/Title Signature Stand		007			
Printed Name/Title Signature S SUM AL O	Date:Date:				

							=	
CLIENT:		Ŀ'nv	IROTEC	H INC.		LOCA	IN NOITA	D:
		ENVIRONMEN 5796 FARMIN	NTAL SCIENTISTS U.S. HIGHWAY IGTON, NEW ME ONE: (505) 632	6 & ENGINEERS 64-3014 VICO 87401			C.□.C. NI	D:
		PHO	ONE: (505) 632	-0615		 		
FIELD REPORT: CLOSURE VERIFICATION						PAGE	PAGE No: of	
LOCATION: NAME: HUERFE						5475		03 <u> 04 07</u> 03 06 07
QUAD/UNIT: D SEC: 1					Y: SS ST:N/	udi ∣	NMENTAL LIST:	
EXCAVATION APPROX.	FT.	x F	T. x	FT. DEI	EP. CUBI	C YAR	DAGE: _	
DISPOSAL FACILITY:			F	REMEDIATIO	ON METH	IOD:		
LAND USE: GRAZE		API Leasi	<u> 30-0</u>	<u> 45 - 267</u>	140 F	ORMATI	on: <u>R</u>	MUGE
FIELD NOTES & REMAR		IT LOCATED	_				_	
DEPTH TO GROUNDWATER: >100		REST WATER ST			EAREST SURFA		CK ON	_
			E 21 D:	<u>~~</u> PPM			ABANDON	
SOIL AND EXCAVATIO	N DF20	CRIPTIUN						INSTALLED
PIT PASSED NO	PIT PASSED NO EXCAVATION NEEDED							
*			FIFI	_D 418.1 CAL	CIII ATIONS			
	TIME	SAMPLE I.D.			mL. FREON	DILUTION	READING	CALC. ppm
SCALE	1320	200 STD					200	200
O EUR	1330	3' BELOW BET	1	5	20		14	56
O FT PIT PERIME	······································		OVM		L DIT	י סס	OFILE	1
EII ERMINI	- 1 Li IV	SAMPL	RESULT		1 11	1 11		
	•	13 Reion		EADSPACE (ppm)				
, i		3						
	1	4 5						
\$ 130								
TOOP TO								
LAB SAMPLES								
TANK SAMPLE ANALYSIS TIME TO THE TANK								
1/2-4								'
			<u> </u>					
TRAVEL NOTES:								
CALLOUT:			01	nsite:				



EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Burlington

Project #:

92115-121-015

Sample No.:

1

Date Reported:

3/7/2007

Sample ID:

Discrete, 3' Below BG Tank

:

Sample Matrix:

Soil

Date Sampled: Date Analyzed: 3/6/2007 3/6/2007

Preservative:

Cool

Analysis Needed:

3/6/2007 TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

Total Petroleum Hydrocarbons

60

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Huerfano Unit # 131

Instrument callibrated to 200 ppm standard. Zeroed before each sample

Analyst

Review



CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal. Date:

6-Mar-07

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
ТРН	100		
	200	200	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

Vicale Haywood

03 (vzlo)

Review Review

3/12/07