

& NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION
AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC NM 87410

(505) 334-6178 FAX: (505) 334-617
nrd.state.nm.us/ocd/District Wadh

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page Revised 11/16/3

	bp America 200 Energy	Production				AGE TES	Γ Well Νο <u>_ [Ε</u> _		
Location	of Well:Unit Lette	er <u> </u>	<u>34</u> Twp <u>3</u>	<u> N_Rge_l(</u>	<u>\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ </u>	0-0 <u>'45-</u> <u>3</u>	5860		
	NAME OF RES	ERVOIR OR POO		TYPE OF PROD. (Oil or Gas)		OF PROD. or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)		
Upper Completion	BLANCE	PC	G/	GAS		OW	TBG		
Lower Completion	BASIN	DK	`GA	`GAS		OW	TBG		
		PRI	E-FLOW SHUT-	IN PRESSU	RE DATA				
Upper	Hour, date shut-in		, ,	Length of time shut-in			Stabilized? (Yes or No)		
Completion	Hour, date shut-in	0/03		72 HOURS			YES		
Lower Completion	08/20	0/03	72 HO	Length of time shut-in 72 HOURS			Stabilized? (Yes or No) YES		
			FLOW TI	EST NO. 1					
Commenced at	- 	T				g (Upper or Lower): REMARKS			
TIME (hour,date)	LAPSED TIME SINCE*	Upper Completion Lower Completion		PROD. ZON TEMP.	1E				
8/26	DAY 1	125	104		вотн	ZONES SH	IUT IN		
8 127	DAY 2	156	106		вотн	ZONES SH	UT IN		
8/28	DAY 3	17a	106		вотн	ZONES SH	UT IN		
8:129	DAY 4	13.1	106		FLOW	UPPER	ZONE		
\$ 130	DAY 5	115	106		FLOW	11	ZONE		
8/31	DAY 6	96	108		FLOW	11	ZONE		
Production ra	ate during test								
Oil:		BOPD based	i on	Bbls. in	Hours_	Grav	GOR		
Gas:		MCFI	PD; Tested thru	(Orifice or M	leter):				
		MID-	TEST SHUT-IN	PRESSURE	E DATA				
Upper Completion	Hour, date shut-in		Length of time shut-in			Stabilized? (Yes or No)			
Lower	Hour, date shut-in	Length of time sl	Length of time shut-in			Stabilized? (Yes or No.)			

(Continue on reverse side)

		<u> </u>	FLOW T	ST NO. 2				
Commenced at (hour, date)**				Zone producing (Upper or Lowr):				
TIME (hour,date)	LAPSED TIME Since**	PRESSURE Upper Completion Lower Completion		PROD. ZONE		REMARKS		
				<u>.</u>	-			
roduction rate	e during test	L	<u> </u>	·	<u> </u>			
il: as:	BOPD t	pased onMCFPD	Bbls. i D:Tested thru (Or	nHour fice or Meter):	sG	rav	_GOR	<u>-</u>
ereby certify	that the informa	ation herein conta 2003	ined is true and	complete to the	bes of my k	nowledge.		
proved Oper dco Oil Conservation Division			Operator	bp Am e rj	ca Prod	luction	Company	New
xico Oil Conse	ervation Division		Ву	Sheri Bra	dshaw	83		*.
Charle	The INCHES	ט הוכץ אי	Title	Field Tec	h		· · · · · · · · · · · · · · · · · · ·	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

Date₁

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

Title

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which wa previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweigh pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested or wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).