

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2007 MAY 25 PM 1:46

1. Type of Well
GAS

2. Name of Operator
CDX RIO, LLC

3. Address & Phone No. of Operator

2010 Afton Place, Farmington, New Mexico 87401 (505) 326-3088

4. Location of Well, Footage, Sec., T, R, M
1850'FNL, 790'FWL, Sec.30, T-26-N, R-5-W, NMPM

RECEIVED
BLM
210 FARMINGTON NM

5. Lease Number
Jicarilla Contract 155
6. If Indian, All. or
Tribe Name
Jicarilla Apache
7. Unit Agreement Name

8. Well Name & Number

Jicarilla 155 #16
API Well No.

10. Field and Pool
30-039-06321

11. Basin Dakota
County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
☐ Notice of Intent	☒ Abandonment ☐ Change of Plans
☒ Subsequent Report	☐ Recompletion ☐ New Construction
☐ Final Abandonment	☐ Plugging ☐ Non-Routine Fracturing
	☐ Casing Repair ☐ Water Shut off
	☐ Altering Casing ☐ Conversion to Injection
	☐ Other

13. Describe Proposed or Completed Operations

5-7-07 MIRU. SDON.

5-8-07 Change out bradenhead valve. ND WH. NU BOP. Test BOP, OK. TOO H w/224 jts 2 3/8" tbg. TIH w/4 1/2" gauge ring to 7220'. (Verbal approval to set first plug @ 7200' from BLM). TOO H. TIH. Establish circ w/5 bbl wtr. Circ hole clean w/50 bbl wtr. Plug #1: pump 27 sx Type III cmt (36 cu.ft.) down tbg to fill inside csg @ 6811-7201' to cover Dakota interval. Load hole w/15 bbl wtr. WOC. SDON.

5-9-07 TIH, tag TOC @ 6813'. TOO H to 6325'. Load csg w/55 bbl wtr. Plug #2: pump 12 sx Type III cmt (16 cu.ft.) inside csg @ 6152-6325' to cover Gallup top. TOO H. TIH, perf 3 sqz holes @ 4762'. TOO H. TIH w/4 1/2" cmt retainer, set @ 4712'. Load tbg w/1.5 bbl wtr. PT tbg to 1500 psi, OK. Load csg w/wtr. Establish injection below cmt retainer w/2 bbl min @ 700 psi. Plug #3: pump 35 sx Type III cmt outside csg; pump 4 sx Type III cmt below cmt retainer inside csg; pump 7 sx Type III cmt above cmt retainer inside csg to 4611' to cover Mesaverde top. TOO H to 3970'. WOC. SDON. (Bryce Hammond, Jicarilla Tribe-BLM on location for plugging).

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed Nancy Oltermann Title Agent Date 5-24-07

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

Date _____

MAY 29 2007

FARMINGTON FIELD OFFICE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCB

- 5-10-07 Load csg w/6 bbl wtr. Plug #4: pump 12 sx Type III cmt (16 cu.ft.) inside csg @ 3797-3970' to cover Chacra top. TOO H to 3070'. Load hole 3 bbl wtr. Plug #5: pump 55 sx Type III cmt (73 cu.ft.) inside csg @ 2274-3070' to cover Pictured Cliffs, Fruitland, Kirtland & Ojo Alamo tops. TOO H. TIH, per 3 sqz holes @ 1193'. TIH w/4 1/2" cmt retainer, set @ 1149'. Load csg w/3 bbl wtr. Attempt to establish circ. Pressure up to 1800 psi, OK. (Verbal approval from Bryce Hammond, Jicarilla Tribe-BLM to change plans). Plug #6: pump 12 sx Type III cmt (16 cu.ft.) inside csg above cmt retainer @ 976-1149'. TOO H. (Bryce Hammond asked that we attempt to circ down 4 1/2" csg & out existing holes @ 713-758'). Pump down 4 1/2" csg & establish circ out existing holes @ 758-773'. Load csg w/30 bbl wtr to establish circ out annulus. Plug #7: pump 248 sx Type III cmt (328 cu.ft.) down 4 1/2" csg from 773' & out bradenhead w/ good cmt returns out bradenhead. WOC. SDON. (Bryce Hammond, Jicarilla Tribe-BLM on location for plugging).
- 5-11-07 ND BOP. Cut off WH. Cmt @ surface in 4 1/2" csg & down 12' in annulus. Fill annulus & set dry hole marker w/30 sx Type III cmt. RD. Rig released.

Well plugged and abandoned 5-11-07