Form 3160-3

UNITED STATES DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

FORM APPROVED

OMB No. 1004-0136

Expires November 30, 2000

		5. Lease Designation and Serial No.						
	APPLICATION FOR PERMIT	NMSF078476						
		6. If Indian, Allottee or Tribe Name						
/		070 Farmington, NM						
/ ,	1a. Type of Work DRILL	7. If Unit or CA, Agreement, Name and No.						
	1b. Type of Well: Oil Well X Gas Well Ot	her Single Zone Multiple Zone	8. Lease Name and Well No.					
	in Type of view.	Militagio Zono	FEDERAL J #1					
_	2. Name of Operator		9. API Well No. 30 045 31818					
	PHOENIX HYDROCARBONS OPERATIN	IG CORPORATION						
		1.1860	10. Field and Pool, or Exploratory					
	3a. Address	3b. Phone Number	<u> </u>					
	P O BOX 3638, MIDLAND, TX 79705	432 686-9869	11. Sec., T., R., M., or Blk. and Survey or Area					
_	4. Location of Well (Footage, Sec, T. R., M, or Survey Description)							
)	At surface: 790' FNL & 890 FEL; A; SEC	/-SEC 11, T-27-N, F	R-8-W					
	At proposed prod. Zone: Same	3						
	14. Distance in miles and direction from nearest town or post of	fice*	12 County or Parish, 13. State					
	20 MILES SOUTH OF BLANCO		SAN JUAN New Mexico 17. Spacing Unit dedicated to this well					
	15. Distance from proposed*	16. No of Acres in lease						
	location to nearest 790' FNL							
	propety or lease line, ft.	320	320 /2					
	(Also to nearest drig. Unit line, if any)	//						
	18. Distance from proposed*	19. Proposed Depth	20. BLM/BiA Bond No. on file					
location to nearest 790' FNL		5450'	BLM NM2887					
	propety or lease line, ft.							
	21. Elevation (Show whether DF, KDB, RT, GL, etc.)	22. Approximate date work will start*	23. Estimated duration 8 DAYS					
	GL 6638'	10/1/2003						
_		24. Attachments						
	• •	nents of Onshore Oil and Gas Order No. 1, shall be attache						
	Well plat certified by a registered surveyor.	rations unless covered by an existin	g bond on file (see					
	A Drilling Plan A Surface Use Plan (if the location is on National Fore							
	o. A canace cae right in the location is oil Mattorial Fold	est System Lands.the 5. Operator certification.						

- SUPO shall be filed with the appropriate Forest Service Office.
- 6. Such other site specific information and/or plans as may be required by the authorized officer

Size of Hole	Grade, Size of Casing	Weight per Foot	Setting Depth	Quantity of Cement
9-7/8"	8-5/8"	23#	238 320	50 SKS HALLIBURTON CLASS "B", CIRC TO SUR
7-7/8"	4-1/2"	10.50#	5450	1455 sks Halliburton "A",w/1/4# Flocele
				& 2% CaCl

SEE ATTACHED APD INFORMATION

25. Signature	Name(Printed/Typed) GREGORY F BAIANO	7-28-03
TIUS VENGINEER		
Approved by (Signature) /s/ David J. Mankiewicz	Name(Printed/Typed)	AUG 2 9 2003
Title	Office	
Application approval does not warrant or certify the applicant holds legal or equit	able title to those rights in the subject lease which wou	ld entitle the applicant to
conduct operations thereon.	·	,
Conditions of approval, if any, are attached.		
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for	or any person knowlingly and willfully to make to any o	lepartment or agency of the
United States any false, ficticious, or fraudulent statements or representations a	s to any matter within its jurisdiction.	

*(Instructions on reverse)

District I Pt) Box 1980, Hobbs, NM 88241-1980 District II 811 South First, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV

State of New Mexico PECEVED

Form C-102 Revised October 18, 1994 Instructions on back

OIL CONSERVATION DIVISION 3 | pm Submit to Appropriate District Office 2040 South Pacheco State Lease - 4 Copies Santa Fe, NM 87505 Fee Lease - 3 Copies 070 Farmington, NM

MENDED REPORT

2040 South Pache	co, Santa F	e, NM 87505				0,0 .	arrii gori,	□ _{AM}	ENDED REPOR	
WELL LOCATION 30 'API' Number 8/8 Poul Code 72319							³ Pool Na			
⁴ Property Code		2319 ederal	Blanco Mesaverde		Well Number					
'OGRID 188483	No.	Pl	hoenix	x Hydrocarbons Op		Name Operating	Name Operating Corp.		'Elevation 6638	
					¹⁰ Surface	Location				
UL or lot no. A	Section 11	Township 27N	Range 8W	Lot Idn	Feet from the 790	North/South line North	Feet from the 890	East/West line East	County San Jua	
	L	1 2/11		tom Ho	le Location I			I nasr	I Sall Jua	
UL or let no.	Section	Township	Range	Lot Ida	Feet from the	North/South line	Feet from the	East/West line	County	
12 Dedicated Acr	es ¹³ Joint	or Infill	L	n Code 14	Order No.					
NO ALLOWA	ABLE WI					UNTIL ALL INT			OLIDATED OR A	
				Y	SE OL OL OL OL OL OL OL OL OL OL OL OL OL	890° 2003	Signify Gregg B Printed Nam Enginee Tale	fy that the information plete to the best of my aiano	knowledge and belief	
		.					I hereby certification was plotted from ander my so correct to the	fy that the well location field notes of actumpervision, and that best of my belief.	al surveys made by me the same is true and	
					·		Generalie No	PROFESSIONAL LANG		

PHOENIX HYDROCARBONS OPERATING CORP. OPERATIONS PLAN Federal J #1RB

- I. 790' from the North line890' from the East lineSection 11-27N-8W San Juan County, N.M.
- II. Field: Blanco Mesaverde Elevation 6638' GR Geology:

San Jose	surface	(fresh water)
Nacimiento	1128'	(fresh usable water)
Ojo Alamo	2079'	(fresh water)
Kirtland	2199'	,
Fruitland	2739'	(coal)
Pictured Cliffs	2950'	(gas)
Lewis	3133'	,
Chacra	3919'	(gas)
Cliff House	4618'	(gas)
Menefee	4645'	(coal)
Point Lookout	5213'	(gas)
Mancos	5391'	
TOTAL DEPTH	5450'	

DO NOT ANTICIPATE ANY ABNORMAL PRESSURE OR H2A

B. Logging Program: IE

IES and GR-NDL & CBL

C. Coring Program:

None

D. Natural Gauges:

Will record all gauges in daily drilling report.

III. Drilling:

A. Mud Program:

Mud from surface to TD. Will use native mud.

Mud weight 8.8-8.9 pp. w/LCM (cedar chips)

when drilling across Mesaverde.

B. Blow Out

A series 900 double gate BOP will be used

Preventer System: with a 2M choke manifold system.

(SEE ATTACHED DIAGRAMS 1 & 2)

The system will include the following items:

- Blind rams

- Pipe rams

- 1 Kill line (2" min.)

- Choke line valve (2" min.)

- 1 Choke line valve

- 2 Chokes

- Upper Kelly cock valve w/handle
- Safety valves and subs to fit drill string
- Pressure gauge on choke manifold
- 2" min. choke line
- Fill-up line above uppermost preventer

IV. Materials:

A. Casing Program:

Hole Size	Depth ,	Casing Size	Weight
9-7/8	Depth 230'320'	8-5/8"	23#
7-7/8	5450'	4-1/2"	10.50#

B. Float Equipment:

8-5/8 surface casing – Larkin Guide Shoe

C. Wellhead Equipment: Casing head rector type "R"

Nom 8' body x 8-5/8" od.

Femal

V. Cementing:

8-5/8" surface casing – use 58 ft3 (50 sks) of Halliburton Standard Class B Portland cement with 2% CaC12 and circulate to surface.

4-1/2" production casing – centralizers will be placed across fresh water zones (1 per joint). The cement will be pumped in two stages with a DV tool set at 2500 ft. Before pumping cement, a 25 bbl mud spaced will be pumped.

1st Stage: Pump calculated volume from caliper log plus 25% excess of Class A Portland cement with fluid loss and lost circulation additives. Drop plug, pressure up on multiple stage cementer and circulate upper part of hole for four hours.

2nd Stage: Pump calculated volume from caliper log plus 25% excess of light cement and circulate out to clean up hole. Then pump calculated volume from caliper log of Class A Portland cement with 2% CaC12 and LCM. Circulate cement to surface.

*A CHRONOLOGICAL LOG WILL BE KEPT.

This will include recorded pump rate, pump pressure, slurry density and slurry volume.