

30-039-25187

5056

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

RECEIVED
JUL - 5 1995

OIL CON. DIV.
DIST. 3

Operator Unocal Oil and Gas Operation Location: Unit D Sec. 14 Twp 27N Rng 7W

Name of Well/Wells or Pipeline Serviced Rincon Unit 133E

Elevation GD6665 Completion Date 02/11/95 Total Depth 280' 280' Land Type* F

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. Water at 60' to 100' Thickness 40'

Depths gas encountered: NONE

Type & amount of coke breeze used: 2800 lbs. Carbo 40

Depths anodes placed: 160' 170' 180' 190' 200' 205' 210' 225' 230' 279'

Depths vent pipes placed: 0' to 300' 280

Vent pipe perforations: 1/8" diameter holes 60' to 280'

Remarks: Lease SF 079298A

First ground bed installed on this location

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

Cathodic Protection Services

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 757-00311	P/L NAME(s), NUMBER(s) Rincon 133 E					
WO #	TOTAL	VOLTS 12.34	AMPS 11.9	= OHMS 1.04	DATE 2-11-95	NAME Don L.

REMARKS (notes for construction log)

2,800 lb of Carbo 40 coke breeze

300 ft. of 1" sch. 200 vent pipe - 220 ft. perforated

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	NO COKE	FULL COKE'
100	.8		295			490			685							
105	.2		300			495			690							
110	.1		305			500			695							
115	.1		310			505			700							
120	.1		315			510			ANODE	DEPTH						
125	.4		320			515			#							
130	.7		325			520			1	279	1.0	27				
135	.6		330			525			2	230	1.5	3.2				
140	.6		335			530			3	225	1.4	2.7				
145	.4		340			535			4	210	2.0	5.				
150	.1		345			540			5	205	1.7	6.1				
155	.9		350			545			6	200	1.9	6.0				
160	1.1		355			550			7	190	1.3	4.1				
165	1.3		360			555			8	180	1.3	3.8				
170	1.6		365			560			9	170	1.0	4.0				
175	1.3		370			565			10	160	.8	2.1				
180	1.3		375			570			11							
185	1.3		380			575			12							
190	1.3		385			580			13							
195	1.3		390			585			14							
200	1.8		395			590			15							
205	1.7		400			595			16							
210	1.9		405			600			17							
215	.8		410			605			18							
220	.9		415			610			19							
225	1.4		420			615			20							
230	1.5		425			620			21							
235	1.4		430			625			22							
240	.7		435			630			23							
245	.2		440			635			24							
250	.1		445			640			25							
255	.2		450			645			26							
260	.2		455			650			27							
265	.1		460			655			28							
270	.1		465			660			29							
275	.1		470			665			30							
280	T&D		475			670										
285			480			675										
290			485			680										

**P.O. BOX 1359 • PHONE 334-6141
AZTEC, NEW MEXICO 87410**

DESCRIPTION OF FORMATION

REMARKS:

REMARKS: Drilled well dry / pipe was wet coming out of the hole / had to drill real quick, to out run the water.

Post-It™ brand fax transmittal memo 7671		# of pages • 3
To Mr. Don Lathicum	From Tom Finck	
Co. UNOCAL	Co. C.P.S. Co.	
Dept. Production-Technician	Phone # 325-1946	
Fax # 632-0338	Fax # 327-9215	