

DATE:

4-26-96

3386

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Location: Unit M Sec. 1 Twp 26 Rng 3

Name of Well/Wells or Pipeline Serviced Sicarilla 96 #7
30-039-06659

Elevation _____ Completion Date 4/26/96 Total Depth 335' Land Type I

Casing Strings, Sizes, Types & Depths 105' 8" PVC Casing

If Casing Strings are cemented, show amounts & types used yes 22 sacks

If Cement or Bentonite Plugs have been placed, show depths & amounts used
None

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 60' Fresh

RECEIVED
FEB 19 1997

Depths gas encountered: None

OIL CON. DIV.
DIST. 8

Ground bed depth with type & amount of coke breeze used: 335'
4100lbs Asbury Coke

Depths anodes placed: 295, 270, 263, 256, 249, 242, 235, 200, 193, 185, 178, 170, 163, 155, 145

Depths vent pipes placed: Surface to 335'

Vent pipe perforations: 160' to 335'

Remarks: No gas encountered during drilling of hole

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2964-U P/L NAME(S), NUMBER(S) Jicarillo # 7
 NO. 2112 TOTAL VOLTS 12.3 AMPS 25.5 OHMS .52 DATE 4-26-96 NAME David Ashworth

REMARKS (NOTE FOR CONSTRUCTION LOG)
 92 Bags 4100 lbs 420-60 Perf 150
 Drilled 340 105 # Casings 27 Bags

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	FULLY COOKED
100			295	2.2	1	490			685			
105			300	1.7		495			690			
110			305	.8		500			695			
115	1.5		310	.8		505			700			
120	1.1		315	.9		510			ANODE	DEPTH	NO	FULLY
125	1.1		320	.6		515					COKE	COOKED
130	1.3		325	.9		520			1	295	2.2	4.3
135	2.4		330	1.7		525			2	270	2.2	4.6
140	3.0		335	TD335		530			3	263	2.7	5.2
145	3.0		340			535			4	256	2.8	5.5
150	2.9	13	345			540			5	249	3.0	5.5
155	3.0		350			545			6	242	3.3	4.8
160	3.2	12	355			550			7	235	2.7	4.6
165	2.7		360			555			8	200	2.6	4.9
170	3.0	11	365			560			9	193	3.1	6.4
175	3.0		370			565			10	185	3.2	7.6
180	3.0	10	375			570			11	178	3.2	7.9
185	3.2		380			575			12	170	3.0	6.9
190	3.1	9	385			580			13	163	3.1	6.4
195	2.9		390			585			14	155	3.1	6.8
200	2.5	8	395			590			15	145	3.0	6.7
205	.8		400			595			16			
210	1.3		405			600			17			
215	1.7		410			605			18			
220	1.3		415			610			19			
225	1.0	7	420			615			20			
230	1.1	6	425			620			21			
235	2.7		430			625			22			
240	3.2	5	435			630			23			
245	2.8		440			635			24			
250	2.9	4	445			640			25			
255	2.7		450			645			26			
260	2.7	3	455			650			27			
265	2.4		460			655			28			
270	2.1	2	465			660			29			
275	1.5		470			665			30			
280	1.0		475			670						
285	1.1		480			675						
290	1.6		485			680						

DISTRIBUTION - ORIGINAL - permanent CPS FILE
 COPY - Division Corrosion Supervisor
 COPY - Region Corrosion Specialist