

## NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410

(505) 334-6178 FAX: (505) 334-6170 http://emnrd.state.nm.us/ocd/District III/3distr

Stabilized? (Yes or No)

Stabilized? (Yes or No.)

Page 1 Revised 11/16/98

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Hour, date shut-in

Hour, date shut-in

Upper

Completion

Completion

in Southeast New Mexico Revised 11/16/98 NORTHWEST NEW MEXICO PACKER-LEAKAGE TES bo America Production Company Operator 200 Energy Ct, Farmington ease Name Schweent Well No 1A Location of Well: Unit Letter C Sec 36 Twp 2 X N Rge 9 W API # 30-0'45- 26683 NAME OF RESERVOIR OR POOL TYPE OF PROD. METHOD OF PROD. PROD.MEDIUM (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper GAS FLOW Completion TBG OTERO Lower GAS FLOW TRG Completion BLANCO MV PRE-FLOW SHUT-IN PRESSURE DATA Hour, date shut-in Length of time shut-in Stabilized? (Yes or No) Upper 72 HOURS Completion 101 YES Length of time shut-in Hour, date shut-in Stabilized? (Yes or No) Lower 72 HOURS Completion YES FLOW TEST NO. 1 Zone producing (Upper or Lower): Commenced at (hour, date)\* LAPSED TIME PRESSURE PROD. ZONE TIME CH mv REMARKS SINCE\* (hour,date) TEMP. **Upper Completion Lower Completion** 177 181 DAY 1 BOTH ZONES SHUT IN 192 209 DAY 2 BOTH ZONES SHUT IN 196 DAY 3 217 BOTH ZONES SHUT IN DAY 4 196 171 FLOW Lower ZONE 161 DAY 5 200FLOW ZONE 154 DAY 6 202 FLOW ZONE Production rate during test BOPD based on Bbls. in Hours Grav. Oil: GOR MCFPD; Tested thru (Orifice or Meter):

(Continue on reverse side)

MID-TEST SHUT-IN PRESSURE DATA

SI press psig

SI press. psig

Length of time shut-in

Length of time shut-in

FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lowr):			
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REA	MARKS	
							·
				,			
Production rat Oil:		pased onMCFPt	Bbls. D:Tested thru (Oi	inHours fice or Meter):	Grav	_GOR	<b>-</b>
		•					
Remarks:	that the inform	ation herein cont	ained is true and	complete to the bes			
Remarks:	that the inform		ained is true and		of my knowledge.		New
Remarks:	that the inform	ation herein cont	ained is true and Operator	complete to the bes	of my knowledge. Production	Company	New

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut-in while the zone which wa previously shut-in is produced.

- 7. Pressures for gas-zone lests must be measured on each zone with a deadweigh pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested or wells which have previously shown questionable test date.
- 24-hour oil zone tests; all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the enc of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).