

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

RECEIVED
SEP 16 PM 12:30

070 Farmington, NM

1. Type of Well

Oil

2. Name of Operator

Vulcan Minerals and Energy Incorporated

3. Address & Phone No. of Operator

c/o NMOCD, 1000 Rio Brazos Road, Aztec, NM 87413

Location of Well, Footage, Sec., T, R, M

1980' 1980'
660' FNL and 660' FEL, Sec. 3D, T-31-N, R-16-W,

5. Lease Number
14-20-603-7346. If Indian, All. or
Tribe Name

Navajo

7. Unit Agreement Name
Horseshoe Gallup8. Well Name & Number
Horseshoe Gallup #479. API Well No.
30-045-1038410. Field and Pool
Gallup11. County & State
San Juan County, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment

Type of Action

☒ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☐ Other -☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut off☐ Conversion to Injection

13. Describe Proposed or Completed Operations

A-Plus Well Service plugged and abandoned the Gallup perforations in this well under an emergency procurement to NMSA 1978, Section 13-1-127. Contract # 03-521-0700-0255.

6-26-03: MOL and RU. Blow down well. Pressure test tubing, OK. Pull and LD rods.

6-27-03: SICP 30 psi; BH flowing water. RU BOP and start to pull 2-3/8" tubing. Found tubing to have heavy paraffin, call for Hot Oil truck - none available. SI well; SD till Monday.

6-30-03: Wait for Hot Oil truck. Pump hot water down tubing and circulate out casing. TOH with 38 joints 2-3/8" tubing. PU casing scraper and TIH to 1194'. TOH. TIH and set 4-1/2" CR at 1072'. PT tubing, OK. PT casing to 500#, OK. Plug #1 with CR at 1072', spot 24 sxs cement inside casing to isolate the Gallup perforations up to 862'. TOH and LD tubing. Perforate at 155'. Establish circulation out BH. Plug #2 with 64 sxs cement pumped down the 4-1/2" casing from 155' to surface, circulate good cement out BH valve. Shut in well and WOC overnight.

7-1-03: Dig out wellhead and cut off. Found cement at surface in 4-1/2" casing and annulus. Set P&A marker with 10 sxs cement. RD and MOL. H. Villanueva with NMOCD was on location.

14. I hereby certify that the foregoing is true and correct.

Signed William F. Clark Title Contract Date 9/13/03
William F. Clark

State Office use)

APPROVED BY _____ Title _____ Date _____
CONDITION OF APPROVAL, if any: _____

NMOCD

SEP 16 2003

FARMINGTON FIELD OFFICE