

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

WELL API NO.

30-031-20695

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

SANTA FE PACIFIC RAILROAD

1. Type of Well

OIL
WELL ☒

GAS
WELL ☐

OTHER: ☐

2. Name of Operator

ROBERT L. BAYLESS

3. Address of Operator

P.O. BOX 168 FARMINGTON, NM 87499

8. Well No.

43

9. Pool name or Wildcat

Miguel Creek Gallup

4. Well Location

Unit Letter M : 330 Feet from the SOUTH Line and 330 Feet from The WEST Line

Section 21 Township 16N Range 6W NMPM McKINLEY County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6402 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO :

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF :

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Robert L. Bayless plugged and abandon this well August 30, 2002. The procedure is attached.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Tom McCarthy

TITLE

ENGINEER

DATE

11/4/02

TYPE OR PRINT NAME

Tom McCarthy

TELEPHONE NO.

(505) 327-2659

(This space for State Use)

APPROVED BY

H. Villanueva

TITLE

DEPUTY OIL & GAS INSPECTOR, DIST. 1

DATE

SEP 25 2003

CONDITIONS OF APPROVAL, IF ANY:

9-25-03

Robert L. Bayless

Plug and Abandon Report

SFPRR No. 43

330' FSL & 330' FWL, Section 21, T16N, R6W

McKinley County, NM

8/30/2002: Rig up JC Well Service. Pressure test tubing with rods and pump in hole. Tested OK. Trip out rods and pump, and used rod count as tally. Tag PBD at 753'. Roll hole with water. Mix and spot 35 sack bottom plug at 751'. Trip out tubing and WOC. Trip in and tag plug at 475'. Pressure test of casing failed. Perforate squeeze holes at 100'. Mix and pump 35 sacks cement. Circulated cement to surface. Rigged down. Henry Villanueva with OCD was on location throughout job and approved cement volumes. Class B cement was used.

Installed abandonment marker and backfilled pit. Cleaned up location.