

754

11-30-045-11593

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 23 Twp 30 Rng 10Name of Well/Wells or Pipeline Serviced RIDDLE B #11

cps 1034w

Elevation 6226' Completion Date 9/66 Total Depth 240' Land Type* N/ACasing, Sizes, Types & Depths N/AIf Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. N/ADepths gas encountered: N/AType & amount of coke breeze used: 3600 lbs.Depths anodes placed: 240', 230', 225', 215', 210', 200', 195', 185', 180', 170'Depths vent pipes placed: N/AVent pipe perforations: N/ARemarks: gb #1.**RECEIVED**
MAY 31 1991
OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

1034.

10

DEPTH, FT.	DRILLER'S LOG	DRILL PIPE TO STRUCTURE			EXPLORING ANODE TO STRUCTURE			DEPTH, TOP OF ANODES
		E	I	R	E	I	R	
10	SANDSTONE				12.0			
20								
30	SANDY CLAY							
40						0.3		
50						1.4		
60						0.4		
70	SANDY SHALE					0.3		
80						0.3		
90		12.0	7.0			0.4		
100						0.3		
10	BLUE SHALE		8.0			1.2		
20			8.0			1.0		
30			10.0			1.3		
40						1.1		
50	SANDY SHALE		10.0			1.3		
60			12.0			1.2		
70						2.3		170
80			14.0			2.1		180-185
90			20.0			1.3		195-200
200						2.0		210
10			22.0			2.1		215
20			22.0			2.2		225
30					3.0		230	
40		12.0	23.0		12.0	2.4	240	

95 # 1
3600 #
Coke

6224

(2) VIBROGROUND 1.0 OHMS



HOUSTON TEXAS