

656

30039-24499

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

2283W

Operator Meridian Oil Location: Unit m Sec. 12 Twp 31 Rng 6Name of Well/Wells or Pipeline Serviced Losa # 225Elevation 6400 Completion Date 10-14-91 Total Depth 455' Land Type FCasing Strings, Sizes, Types & Depths 60" sch 40 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NODepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NO

OIL CON. DIV.]

DIST. 3

Ground bed depth with type & amount of coke breeze used:

455' Ashbury 82 sacksDepths anodes placed: 425 415 405 395 385 355 345 336 326 316 306 295 27Depths vent pipes placed: 155 145 415Vent pipe perforations: 1" apart Perforated bottom 310'Remarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2283	P/L NAME(s), NUMBER(s) Losa # 225					DATE 10-14-91	NAME L.S.E.
NO # M609	TOTAL 12.53	VOLTS 23.4	AMPS .53				
REMARKS (notes for construction log)							

No water table. Dry hole. Set 60' of 8" PVC casing, perforated bottom 310' from 2nd anode.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	#		ANODE	#		ANODE	#		ANODE	#	
100	3.0		295	2.6	-12	490			685			
105	2.9		300	2.4		495			690			
110	2.9		305	2.2	-11	500			695			
115	2.8		310	2.2		505			700			
120	2.9		315	2.6	-10	510			ANODE	DEPTH	NO	FULL
125	3.2		320	2.6		515			*		COKE	COKE
130	3.1		325	2.5	-9	520			1	425	2.5	4.5
135	2.7		330	2.2		525			2	415	2.7	5.0
140	1.8		335	2.1	-8	530			3	405	2.7	5.0
145	2.2	-15	340	2.4		535			4	395	2.3	4.1
150	2.6		345	2.5	-7	540			5	365	2.5	4.2
155	2.4	-14	350	2.4		545			6	355	2.5	4.4
160	1.9		355	2.5	-6	550			7	345	2.7	4.6
165	1.8		360	2.5		555			8	336	2.3	4.3
170	1.7		365	2.1	-5	560			9	326	2.6	4.7
175	1.6		370	1.6		565			10	316	2.7	4.6
180	1.4		375	1.5		570			11	306	2.2	4.2
185	1.3		380	1.6		575			12	295	2.7	4.7
190	1.4		385	1.7		580			13	275	2.6	4.2
195	1.3		390	2.1		585			14	155	2.6	5.0
200	1.4		395	2.5	-4	590			15	145	2.2	5.1
205	1.3		400	2.5		595			16			
210	1.2		405	2.5	-3	600			17			
215	1.5		410	2.6		605			18			
220	1.6		415	2.6	-2	610			19			
225	1.5		420	2.6		615			20			
230	1.6		425	2.3	-1	620			21			
235	1.5		430	2.0		625			22			
240	1.3		435	2.2		630			23			
245	1.1		440	2.4		635			24			
250	1.1		445	2.3		640			25			
255	1.0		450	2.3		645			26			
260	1.0		455	TD	455	650			27			
265	1.4		460			655			28			
270	2.4		465			660			29			
275	2.7	-13	470			665			30			
280	2.7		475			670						
285	2.6		480			675						
290	2.5		485			680						

DISTRIBUTION - original - permanent CPS FILE
 copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist