

#5 → 30-045-09552
#1A → 30-045-26639

4900

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit NW Sec. 17 Twp 30 Rng 10

Name of Well/Wells or Pipeline Serviced SCHUMACHER #5, #1A

cps 809w

Elevation 6386' Completion Date 10/11/68 Total Depth 400' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 240'

Depths gas encountered: N/A

Type & amount of coke breeze used: 7320 lbs.

Depths anodes placed: 369', 363', 317', 311', 305', 299', 293', 287', 281', 275', 26

Depths vent pipes placed: 369' OF 3/4" HOSE

Vent pipe perforations: 340'

Remarks: gb#1

RECEIVED

MAY 31 1991

OIL CON. DIV

DIST. 2

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

Date 10-11-68

Insert # 66 = 260'

Well Name <u>Schumacher #5</u>			CPS No. <u>809W</u>		
Location <u>NW 17-30-10</u>			Work Order No. <u>184-52231-50-20</u>		
Anode Hole Depth <u>400</u>	Total Drilling Rig Time <u>28 1/2 Hrs</u>	Type & Size Bit Used <u>7 7/8 842183 = 400</u>		No. Sacks Mud Used <u>1</u>	
No. Sacks Lost Circulation Mat'l Used <u>0</u>	Anode Depth				
	#1 <u>369</u>	#2 <u>363</u>	#3 <u>317</u>	#4 <u>311</u>	#5 <u>305</u> #6 <u>299</u>
Total Lbs. Coke Used <u>7320</u>	Anode Output (Volts)				
	#1 <u>3.4</u>	#2 <u>3.7</u>	#3 <u>3.7</u>	#4 <u>4.3</u>	#5 <u>5.3</u> #6 <u>6.0</u>
Total Circuit Resistance	No. Ft. Surface Cable Conduit				
Volts <u>11.2</u> Amps <u>15.5</u> Ohms <u>0.72</u>	<u>2253 DWH No. 1 = 404 Surface 4256</u>				

Drilling Log (Attach Hereto). ☐ 7 293 8 287 9 281 10 275 11 269 12 263

Remarks: 7 6.2 8 6.1 9 5.4 10 5.5 11 5.5 12 4.6

Life 600' NE = 1. - 2
3/4" Hose to No. 1 Anode Perforated 340'
50 lbs Barafas

All Construction Completed
Forrester
(Signature)

GROUND BED LAYOUT SKETCH



