## UNITEDSTATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORMA	PPROVED
	o. 1004-0137
Expires:	March 31, 200

## SUNDRY NOTICES AND REPORTS ON WELLS

5. Lease Serial No.	
NMSF 078998	
C ICI. diam Allagan and Talla Managar	

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			6. If India	6. If Indian, Allottee or Tribe Name		
SUBMIT IN TRIPLICATE - Other instructions on reverse side.  1. Type of Well				277 It Unit of CA/Agreement, Name and/or No.		
				SAN JUAN 32-7 UNIT RECEIVED  8. Well Name and No.		
2. Nameof Operator				<u>UAN 32-7 UNIT 17A</u>		
ConocoPhillips Company			9. API W			
3a. Address 3b. PhoneNo. (include area code)			Y	30-045-33832		
PO BOX 4289 Farmingto		326-9597		and Pool, or Exploratory Area  Mesaverde		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 815 SOUTH 1665 EAST UL: O, Sec: 17, T: 31N, R: 7W			11. Cou	11. County or Parish, State SAN JUAN		
12. CHECK A	PPROPRIATE BOX(ES)TO INDICATE	NATURE OF NO		OR OTHER DATA		
TYPEOF SUBMISSION		TYPEOF ACT	TON			
Notice of Intent	Acidize Deepen AlterCasing FractureT	Produ	action (Start/Resume)	Water Shut-Off Well Integrity		
X Subsequent Report	Casing Repair New Con	struction Reco	nplete	X OtherCompletion		
	Change Plans Plug and A	Abandon 🔲 Temp	orarily Abandon	Detail		
Final Abandonment Notice	Convert to Injection Plug Back	Wate	Disposal			
determined that the site is read 11/20/07 RU W/L. Run W/L. No remediation no 04/19/07 Install frac valva Rigless Completion: 04/25/07 Perf LMF/PTL Frac: Pump 10 bbl 15% Perf CLH/UMF 5180' - 5 Frac: Pump 10 bbl 15% Perf Lewis 4550' - 5100' Frac w/75Q 20# Linear 07/13/07 MIRU Key #11 07/18/07 Run flow MV fl	nal Abandonment Notices shall be filed only after y for final inspection.)  GR/CCL/CBL from 6199' (PBTD) excessary per Jim Lovato (BLM) are. PT frac valve and casing to 41.  5650' - 6090', 28 holes, 0.34" di. HCL ahead of 60Q Slickfoam @ 5586', 30 holes, 0.34" dia., 1 spf. HCL ahead of 60Q slickfoam @ 500 holes, 0.34" dia., 1 spf. HCL ahead of 60Q slickfoam @ 500 holes, 0.34" dia., 1 spf. HCL ahead of 60Q slickfoam @ 500 holes, 0.34" dia., 1 spf. HCL ahead of 60Q slickfoam @ 500 holes, 0.34" dia., 1 spf. ND master valve. NU BOP -PT ow test. RIH w/181 jnts 2 3/8", 4.5 Turn over to production.	to surface. TOO nd Steve Hayder 00#/15 min. Go a., 1 spf 50 to 54 bpm w/ 000# 20/40 Brac ok. Clean out to	C @ 3330' (7" so (OCD) 04/18/0 od test. (100,240# 20/40 dy sand. Flow we PBTD on 07/17	et @ 3315 - no overlap). RD  O Brady sand.  Brady sand.  ell 3 days.		
14. I hereby certify that the fore Name (Printed/Typed)	egoing is true and correct	1		VIOI.O		
Juanita Farrell		Title Regulate	ory Specialist			
Signature	famel	Date 07/23/20	007			
	THIS SPACE FOR FEDERAL	OR STATE O	FFICE USE			
Approved by		Title		Date		
certify that the applicant holds leg which would entitle the applicant		lease Office	**************************************			
Title 18 U.S.C. Section 1001 and Ti States any false, fictitious or frau	itle 43 U.S.C. Section 1212, make it a crime for a dulent statements or representations as to any	ny person knowingly a matter within its juris	nd willfully to make to diction.	any department or agency of the United  ACCEPTED FOR RE		

(Instructions on page 2)

ACCEPTED FOR RECORD