Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

'RECEWE

FORM APPROVED OMB No. 1004-0135 Expires November 30, 2000

5. Lease Serial No.

| 14 | -20 | ക്ഷ | 3. | .20 | 1 |
|----|-----|-----|----|-----|---|

| Do not the this famous to tall on wells | 14-20-603-2034 36. If Indian, Allottee or Tribe Name Navajo Tribal | |
|---|--|--|
| Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals | | |
| SUBMIT IN TRIPLICATE Dither instructions on reverse side | Zan If Unit or CA/Agreement, Name and/or No. | |
| 1. Type of Well Gas Well Other () () | 8. Well Name and No. | |
| 2. Name of Operator | Navajo TI "F" #101 | |
| Hart Oil and Gas Inc. | 9. API Well No. | |
| 3a. Address P.O. Box 307 - Farmington, N. M. 87499 3b. Phone No. (include area code) (505) 326-1163 | 30045(11116)00S1 10. Field and Pool, or Exploratory Area | |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) | Horseshoe Gallup | |
| 660' FNL & 660' FWL TWP/LAT RGE/LON SEC QTR 31N 17W 4 NWNW | 11. County or Parish, State San Juan, N. M. | |
| 12. CHECK APPROPRIATE BÖX(ES) TO INDICATE NATURE OF NOTICE, R | EPORT, OR OTHER DATA | |
| TYPE OF SUBMISSION TYPE OF ACTION | | |
| Acidize Deepen Production (Star | t/Resume) 🔲 Water Shut-Off | |
| Notice of Intent | Well Integrity | |
| Subsequent Report Casing Repair New Construction Recomplete | Other | |
| Change Plans Plug and Abandon Temporarily Ab | andon | |
| Final Abandonment Notice Convert to Injection Plug Back Water Disposal 13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of a | | |
| testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including recladeretmined that the site is ready for final inspection.) We plan on plugging this well by placing cement from the top of the perfs to 10 above the top of the Gallup with some extra cement for shrinkage. We will comback and tag to make sure cement is at least 100' above top of the Gallup. We will then perforate at 90 feet which is 50' below the surface casing and circulated cement and fill the production casing and annulus to 50' below the bottom of the surface casing. We will let the cement dry and if necessary, add to top off at surface casing: 10 | o' e ilate <u>V 13 14 75 76</u> | |
| 14. I hereby certify that the foregoing is true and correct | | |
| Name (Printed/Typed) | E-PRESIDENT | |
| Signature Juna VI Sained Date 10. | /03/03 | |
| THIS SPACE FOR FEDERAL OR STATE OFFICE USE | | |
| Approved by Original Signed: Stephen Mason Title | Date OCT 1 5 2003 | |
| Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable ritle to those rights in the subject lease which would entitle the applicant to conduct operations thereon. | | |