## <u>District 1</u> 1625 N French Dr., Hobbs, NM 88240 District III 100 Rio Brazos Road, Aztec, NM 87410 District IIII <u>District IV</u> 1220 S. St Francis Dr , Santa Fe, NM 87505

#### State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Form C-144

June 1, 2004

### 1220 South St. Francis Dr. Santa Fe, NM 87505 Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tan Type of action. Registration of a pit of	ık covered by a "general plan"? Yes 🛛 N or below-grade tank 🔲 Closure of a pit or below-g	No □ grade tank
Operator: Chevron Production Co. Address: 322 County Road 3100, Aztec, NM 87410	ne: (505) 334-7117 e-mail addres	ss: MArcher@chevron.com
Facility or well name: Rincon #31 API #: 30-039-06  County: Rio Arriba Latitude  Surface Owner: Federal State Private Indian	5766         U/L or Qtr/Qtr         P Sec           36.523198         Longitude         -107.52013	
Pit  Type: Drilling ☐ Production ☒ Disposal ☐  Workover ☐ Emergency ☐  Lined ☒ Unlined ☐  Liner type: Synthetic ☐ Thickness 2 Layers of 6mil plastic with thin fiberglass layer between ☐ Clay ☐  Pit Volume 4 bbl	Below-grade tank  Volumebbl Type of fluid:  Construction material:  Double-walled, with leak detection? Yes	not, explain why not.
Depth to ground water (vertical distance from bottom of pit to seasonal high water elevation of ground water.)	Less than 50 feet 50 feet or more, but less than 100 feet 100 feet or more	(20 points) (10 points) ( 0 points) 0
Wellhead protection area: (Less than 200 feet from a private domestic water source, or less than 1000 feet from all other water sources.)	Yes No	(20 points) ( 0 points) 0
Distance to surface water: (horizontal distance to all wetlands, playas, irrigation canals, ditches, and perennial and ephemeral watercourses.)	Less than 200 feet 200 feet or more, but less than 1000 feet 1000 feet or more	(20 points) (10 points) ( 0 points) 10
	Ranking Score (Total Points)	10
If this is a pit closure: (1) Attach a diagram of the facility showing the pit your are burying in place) onsite  offsite  If offsite, name of facility remediation start date and end date. (4) Groundwater encountered: No  (5) Attach soil sample results and a diagram of sample locations and excava Additional Comments:  Soil passed TPH standard of 1000 ppm using USEPA Method 418.1 and the Soil passed TPH standard of 1000 ppm using USEPA Method 418.1, the 1	Envirotech's Landfarm #2 . (3) Attach a general Yes  If yes, show depth below ground surface_tions.  the 100ppm OVM standard 3 feet below lowest layer.	er of liner.  the liner.  cons. DIV UIDL-3 Av.
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline  Date	Signature	at the above-described-pit or below-grade tank rnative OCD-approved plan
Approval: Printed Name/Title Signature Signature	OCT 2 9 20	007

CLIENT:	Envirot	ECH INC.		LOCATION NO:
CLIENT		entists & engineers		C.D.C. ND:
92270-170-046	CTATE FARMINGTON, N	GHWAY 64-3014 EW MEXICO 87401 5) 632-0615		C.U.C. 1801
FIELD REPOR	RT: CLOSURE	VERIFICAT	'ION	PAGE No: of
LOCATION: NAME. Ring	CON WELL #. 3	PIT.	TAL	DATE STARTED 09/18/07 DATE FINISHED. 09/24/07
QUAD/UNITY SEC:	36 TWP 27N RNG 7W	PM· NM CNTY:	$S1 \sim 1$	NVIRONMENTAL PECIALIST ENH/2TK
		The state of the s		
DISPOSAL FACILITY:	FT. x FT. x	FT. DEEP REMEDIATION	METHOD	YARDAGE:
LAND USE: Grozin		E-290-28		IATION:
FIELD NOTES & REMAR			FT 3	FROM WELLHEAD
	NEAREST WATER SOURCE:	>/ofo NEARES	T SURFACE	WATER: 205
NMOCD RANKING SCORE:	// NMBCD TPH CLOSURE STD:	PPM		CHECK ONE
SOIL AND EXCAVATION	N DESCRIPTION:	,	1	PIT ABANDONED STEEL TANK INSTALLED
Lined Wa	ter between the	liners		TELL THAN INSTRUCTED
9x6x2				
	_			
auger de	fusel @ 2.5'	bolow lines	(sam	do tone)
contamina	etwo in sort unte	f approx of dea FIELD 418.1 CALCULA	ep the	n Clears.
	TIME SAMPLE ID LAB	No: WEIGHT (g) mL	FREON DILU	TION READING CALC. ppm
SCALE	200 std	2	0 4	111 444
O FT	2.5 balon 2	5 0	0 4	9 36
PIT PERIM	ETER O'RES	VM ULTS	PIT I	PROFILE
	SAMPLE	FIELD HEADSPACE PID (ppm)		
Ver 1	N 1 2 1 351	37.4		1
. 600	3 4			
	5			
1000	,		\ _	
1				Ta
7		AMPLES		
	ID ANA	ALYSIS TIME		
				*\$_
TRAVEL NOTES. CALLOUT		ONSITE.		

1245 1300

36.523198 - 107.52013



#### EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Chevron Production

Project #:

92270-170-046

Sample No.:

1

Date Reported:

10/1/2007

Sample ID:

Composite, Inside Lined Pit

1

9/18/2007

Sample Matrix:

Soil

Date Sampled: Date Analyzed:

9/18/2007

Preservative:

Cool

Analysis Needed:

TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Total Petroleum Hydrocarbons** 

440

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Rincon #31

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

Review

**Robert Konig** 

Printed

Nicole Hayworth

Printed



# CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Cal. Date: 18-Sep-07

Printed

Parameter	Standard Concentration mg/L	Concentration Reading mg/L	
ТРН	100		
	200	193	
	500		
	1000		

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

1/1/	10/02/07
Analyst	Date /
Robert Konig Printed	
Mical Hayras	10/02/07
Review	Date
Nicole Hayworth	



#### EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Client:

Chevron Production

Project #:

92270-170-046

Sample No.:

2

Date Reported:
Date Sampled:

10/1/2007

Sample ID:

Discrete, 3' below Pit

9/24/2007

Sample Matrix: Preservative:

Soil Cool Date Analyzed:
Analysis Needed:

9/24/2007 TPH-418.1

Condition:

Cool and Intact

		Det.
	Concentration	Limit
Parameter	(mg/kg)	(mg/kg)

**Total Petroleum Hydrocarbons** 

36

5.0

ND = Parameter not detected at the stated detection limit.

References:

Method 418.1, Petroleum Hydrocarbons, Total Recoverable, Chemical Analysis

of Water and Waste, USEPA Storet No. 4551, 1978.

Comments:

Rincon #31

Instrument calibrated to 200 ppm standard. Zeroed before each sample

Analyst

Review

David Young

Printed

Nicole Hayworth



24-Sep-07

1000

Cal. Date:

# CONTINUOUS CALIBRATION EPA METHOD 418.1 TOTAL PETROLEUM HYDROCARBONS

Parameter	Standard Concentration mg/L	Concentration Reading mg/L
ТРН	100	
	200	204
	500	

The accepted percent relative deviation (%RSD) of the calibration factor is less than 20% over the working range.

Alfa	10-2-07
Analyst	Date
David Young	
Printed	
Mical Hunren	10/02/07
Review	Date
Nicole Hayworth	
Printed	



## EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Chevron	Project #:	92270-170-046
Sample ID:	In Pit	Date Reported:	09-19-07
Laboratory Number:	43103	Date Sampled:	09-18-07
Chain of Custody:	3400	Date Received:	09-18-07
Sample Matrix:	Soil	Date Analyzed:	09-19-07
Preservative:	Cool	Date Extracted:	09-19-07
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
_	,	
Benzene	ND	0.9
Toluene	140	1.0
Ethylbenzene	152	1.0
p,m-Xylene	1,250	1.2
o-Xylene	573	0.9
Total BTEX	2,120	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	97.0 %
	1,4-difluorobenzene	97.0 %
	Bromochlorobenzene	97.0 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Rincon 31

Analyst

Christien Waster



### EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	N/A	Ę	Project #:		N/A
Sample ID.	09-19-BTEX QA/QC		Date Reported:		09-19-07
Laboratory Number.	43096	I	Date Sampled:		N/A
Sample Matrix:	Soil	1	Date Received:		N/A
Preservative:	N/A	1	Date Analyzed:		09-19-07
Condition:	N/A	,	Analysis:		BTEX
Calibration and  Detection Limits (ug/L)	A-Cal RF.	C-Cal RF: Accept, Rang	%Diff. e 0 - 15%	Blank Conc	Detect.
Benzene	2 8056E+007	2.8113E+007	0.2%	ND	0.1
Toluene	7.8076E+007	7.8233E+007	0.2%	ND	0.1
Ethylbenzene	7.1118E+007	7.1261E+007	0.2%	ND	0.1
p,m-Xylene	1.5287E+008	1.5318E+008	0.2%	ND	0.1
o-Xylene	7 3066E+007	7.3212E+007	0.2%	ND	0.1
Duplicate Conc. (ug/Kg)	Sample	Duplicate	%Diff.	Accept Range	Detect Limit
Duplicate Conc. (ug/Kg)  Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene	2.9 69.5 22.4 995 83.7	2.9 69.3 22.2 994 83.5	%Diff. 0.0% 0.3% 0.9% 0.1% 0.2%	Accept Range 0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	0.9 1.0 1.0 1.2 0.9
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (ug/Kg)	2.9 69.5 22.4 995 83.7	2.9 69.3 22.2 994 83.5	0.0% 0.3% 0.9% 0.1% 0.2%	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	0.9 1.0 1.0 1.2 0.9
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (ug/Kg)	2.9 69.5 22.4 995 83.7	2.9 69.3 22.2 994 83.5	0.0% 0.3% 0.9% 0.1% 0.2% Spiked Sample	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30%	0.9 1.0 1.0 1.2 0.9
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene  Spike Conc. (ug/Kg)  Benzene Toluene	2.9 69.5 22.4 995 83.7 Sample	2.9 69.3 22.2 994 83.5 Amount Spiked 50.0 50.0	0.0% 0.3% 0.9% 0.1% 0.2% Spiked Sample 52.9 119	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% % Recovery	0.9 1.0 1.0 1.2 0.9 Accept Range
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene Spike Conc. (ug/Kg) Benzene Toluene Ethylbenzene	2.9 69.5 22.4 995 83.7 Sample 2.9 69.5 22.4	2.9 69.3 22.2 994 83.5 Amount Spiked 50.0 50.0 50.0	0.0% 0.3% 0.9% 0.1% 0.2% Spiked Sample 52.9 119 72.3	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% % Recovery 100.0% 99.8% 99.9%	0.9 1.0 1.0 1.2 0.9 Accept Range 39 - 150 46 - 148 32 - 160
Benzene Toluene Ethylbenzene p,m-Xylene o-Xylene  Spike Conc. (ug/Kg)  Benzene Toluene	2.9 69.5 22.4 995 83.7 Sample	2.9 69.3 22.2 994 83.5 Amount Spiked 50.0 50.0	0.0% 0.3% 0.9% 0.1% 0.2% Spiked Sample 52.9 119	0 - 30% 0 - 30% 0 - 30% 0 - 30% 0 - 30% % Recovery	0.9 1.0 1.0 1.2 0.9 Accept Range

ND - Parameter not detected at the stated detection limit.

References<sup>1</sup>

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic and Halogenated Volatiles by Gas Chromatography Using Photoionization and/or Electrolytic Conductivity Detectors, SW-846, USEPA December 1996.

Comments:

QA/QC for Samples 43096 - 43105

Analyst

Review

## CHAIN OF CUSTODY RECORD

Chevron				Project Name / Location.  Rincon  31						ANALYSIS / PARAMETERS													
Client Address.				Project Name / Location.  Lincon  Sampler Name:  Robert / Nicole H  Client No.: 92279-170-\$46					8015)	1 8021)	8260)	S											
Client Phone No.:				Client No. 92279-179-946						BTEX (Method 8021)	VOC (Method 8260)	RCRA 8 Metals	Cation / Anion		TCLP with H/P		TPH (418 1)					Sample Cool	Sample Intact
Sample No Identification	on Dat	te	Sample Time	Lab No.	Sample Matrix	No./Volu	me Preser	rvative	TPH (Method 8015)	ВТЕХ	NOC (	RCRA	Cation	RCI	TCLP	РАН	TPH (					Sampl	Sampl
INP	it %	8 /2	23\$	43103	So.1					X													-
															and a second								
Relinquished by (Signature)						Date 9/18	Time /550		Received by: (Signature)  Received by: (Signature)										Date 9/18/07			me 550	
Relinquished by	y (Signature)						/ 	(	leceive	ed by:	(Signa	ature)	<u>'</u>	$\omega$		ومعروب					<u> </u>		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Relinquished by. (Signature)										Received by. (Signature)												-	
							IRC	7	EC	升		)C										'	
				5790	6 U S. Hıg	Jhway 64			, New		o 874(	01 • (50	<b>i</b> )5) 632	2-0615	;						,		