UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

	Sundry Notices and Reports on	Wells		
1.	Type of Well OIL	RECEIVED DEC 0 6 2007	5. 6.	Lease Number NOG 01 101555 If Indian, All. or Tribe Name
2.	Name of Operator D. J. Simmons, Inc.	Bureau of Land Management Farmington Field Office	7.	Allotment 011391 Unit Agreement Name
3.	Address & Phone No. of Operator 1009 Ridgeway Place, Suite 200	204 2752	8.	Well Name & Number Blanco Wash 27 #2
4.	Farmington, New Mexico 87401 (505) 326 Location of Well, Footage, Sec., T, R, M 642' FNL, 1741' FWL, Sec.27, T-24-N, R	, M	9. 10.	API Well No. 30-045-34107 Field and Pool
			11.	Lybrook Gallup County and State
				San Juan Co, NM
	X Subsequent Report Pl Ca: Final Abandonment Al			RCVD DEC 11'07 OIL CONS. DIV. DIST. 3
13.	Describe Proposed or Completed Op	perations		
	9 5/8" 36# J-55 ST&C calcium chloride, 0.25 9-8-07 Plug down @ 2:15 a.m. 9 low, 1500 psi high, OF	-7-07. Drill 12 1/4" surface hole to 428'. Circ hole csg, set @ 423'. Pump 20 bbl wtr ahead. Cmtd v pps Superflake (318 cu.ft.). Circ 25 bbl cmt to su 0-8-07. WOC. NU BOP. PT choke manifold, pipe X. PT csg to 500 psi, failed. PT csg to 500 psi, OK. NU BOP. TIH w/7 7/8" to hole clean.	v/270 sx Tygarface. e rams, blind	ope III cmt w/2% I rams to 250 psi
	APD ROW related	Continued on back		EARMINGTON FIELD OFFICE
	I hereby certify that the foregoing is	true and correct.		
Sig	ned Hodning 2 Seale	Title Operations Manager		Date <u>12-5-07</u> .
(Th	nis space for Federal or State Office use PROVED BY ONDITION OF APPROVAL, if any:	Title		Date

Title 18 U S C. Section 1001, makes it a clime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

Report PT on 5/2 csg next report

9-21-07 Circ hole clean. TOOH. TIH w/141 jts 5 ½" 17# J-55 ST&C csg, set @ 5595". Circ hole clean. TOOH. Pump 20 bbl chemical wash ahead. Cmtd first stage w/250 sx Premium Light cmt w/5 pps Gilsonite, 0.125 pps Cellophane (450 cu.ft.). Tailed w/285 sx 50/50 poz w/3.5 pps Phenoseal, 0.2% CFR-3, 0.6% Halad-9 (407 cu.ft.). Circ 3 bbl cmt to surface. WOC. Stage tool set @ 1600". Pump 20 bbl wtr ahead. Cmtd second stage w/250 sx Premium Light cmt w/5 pps Gilsonite, 0.125 pps Cellophane (485 cu.ft.). Tailed w/100 sx Premium cmt w/3 pps Gilsonite, 0.4% Halad-344, 0.1% HR-5 (124 cu.ft.). Circ 5 bbl cmt to surface. Plug down @ 1:15 p.m. WOC. (Larry Pixley, BLM on location for cementing). ND BOP. NU WH. RD. Rig released.