

30-039-24853

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit Sec. 30 Twp 28 Rng 6
 Name of Well/Wells or Pipeline Serviced San Juan 30-6 Unit No. 411
Well
 Elevation Completion Date 11-27-90 Total Depth 495' Land Type P
 Casing Strings, Sizes, Types & Depths 8" dia. PVC to a depth
of 20' below grade.
 If Casing Strings are cemented, show amounts & types used 5 each 90 lb.
bags of Sackrete.
 If Cement or Bentonite Plugs have been placed, show depths & amounts used
NA = None
 Depths & thickness of water zones with description of water: Fresh, Clear,
 Salty, Sulphur, Etc. Damp Grey Sandstone from 180' to 210'
Muddy - Fresh Water
 Depths gas encountered: None - NA
 Ground bed depth with type & amount of coke breeze used: 495' Deep with
99.9% Carbon Coke Breeze (Loresco SWB) = 5,700 lbs.
 Depths anodes placed: 195', 155', 280', 290', 350', 360', 370', 380', 390', 400', 410', 420'
 Depths vent pipes placed: 0 to 495' deep
 Vent pipe perforations: From 195' to 495' deep
 Remarks:

RECEIVED
 DEC 3 1990
 OIL CON. DIV.
 DIST. 9

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
 If Federal or Indian, add Lease Number.