

30-045-20002

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit P Sec. 13 Twp. 26 Rng. 09

Name of Well/Wells or Pipeline Serviced _____

Tibbet Fed. #2

Elevation _____ Completion Date 4/27/94 Total Depth 418' Land Type F

Casing Strings, Sizes, Types & Depths 4 1/2" Set 98' of 8" PVC Casing.

NO GAS, WATER, or Boulders were encountered during casing.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 22 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 120', AND A MAJOR

WATER VEIN AT 210'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 418' DEPTH.

USED 55 SACKS OF LOFESCO SW (5500#)

Depths anodes placed: 343', 336', 329', 322', 315', 308', 301', 294', 215', 145', 158', 151', 144', 137', + 130'.

Depths vent pipes placed: SURFACE TO 418'.

Vent pipe perforations: BOTTOM 300'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.