

30-045-29011

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit M Sec. 20 Twp 26 Rng 09

Name of Well/Wells or Pipeline Serviced _____

Huetfano #500

Elevation _____ Completion Date 4/23/94 Total Depth 422' Land Type F

Casing Strings, Sizes, Types & Depths 4 1/2 Set 99' of 8" PVC Casing.

NO GAS, WATER, or Boulders were encountered during casing.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 22 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 125'. A WATER SAMPLE

WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 422' DEPTH.

Used 56 SACKS OF LOTESCO SW (5600#)

Depths anodes placed: 385', 340', 330', 320', 310', 299', 290', 280', 270', 260', 250', 185', 165', 155', + 142'.

Depths vent pipes placed: SURFACE TO 422'

Vent pipe perforations: BOTTOM 305'.

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.