

30-045-22725

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit P Sec. 04 Twp 31 Rng 10

Name of Well/Wells. or Pipeline Serviced _____

Lucerne A #10

Elevation 6134 Completion Date 7/28/94 Total Depth 388' Land Type P

Casing Strings, Sizes, Types & Depths 7/27 Set 99' of 8" PVC Casing.

NO GAS OR WATER, BUT 36' OF BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 35 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 125' AND MORE

FRESH WATER AT 305'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 388' DEPTH.

USED 96 SACKS OF ASBURY 218R (4800#)

Depths anodes placed: 370', 362', 354', 346', 338', 318', 310', 302', 294', 280', 195', 164', 156', 148', + 140'

Depths vent pipes placed: SURFACE TO 388'

Vent pipe perforations: BOTTOM 270'

Remarks: _____

RECEIVED
JAN 20 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.