

4248W

18-30-045-07513

1-30-045-07512

21-30-045-25362

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meridian Oil Inc. Location: Unit A Sec. 13 Twp 28 Rng 10

Name of Well/Wells. or Pipeline Serviced _____

McCLANAHAN #18, #1, AND #21Elevation _____ Completion Date 5/12/94 Total Depth 398' Land Type FCasing Strings, Sizes, Types & Depths 5/11 Set 99' of 8" PVC Casing.NO GAS OR BOULDERS, BUT WATER AT 45' WAS ENCOUNTERED DURING CASINGIf Casing Strings are cemented, show amounts & types used CementedWITH 30 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONEDepths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 135' AND MORE FRESH WATER AT 370'. A WATER SAMPLE WAS TAKEN.Depths gas encountered: NONEGround bed depth with type & amount of coke breeze used: 398' Depth.Used 103 SACKS OF Asbury 218R (5150#)Depths anodes placed: 345', 335', 320', 310', 290', 275', 265', 235', 225', 215', 205', 190', 180', 170', + 145'.Depths vent pipes placed: SURFACE TO 398'.Vent pipe perforations: BOTTOM 275'.

Remarks: _____

RECEIVED
JAN 20 1995OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.