

(SUBMIT IN TRIPLICATE)

			_
	 -		
	2	7	
			X

MAIN OFFICE UNITED STATES DEPARTMENT OF THE INTERIOR 1959 JUN 25 AIGESLOSIFAL SURVEY

and Office Santa Fe
ease No. 078091
Inte Gov!t. Douthit

NOTICE OF INTENTION TO SELDRILL OR REPAIR WELL NOTICE OF INTENTION TO SELDRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING. SUBSCULENT REPORT OF ABANDONMENT SUBSCULENT REPORT OF ABANDOMENT SUBSCULENT REPORT OF ABANDONMENT SUBSCULET, SUBSCULE	I NOTICE OF INTENTION TO TEST WATER SUIT OFF	SUBSEQUENT REPORT OF WATER SHUT-OFF SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO ABANDON WELL COMPLICATION SUMMARY		COLUMN TO THE CO
Completion Summary Complet	1	
Douthit Well No. B-19 is located 1980. ft. from [N] line and .660. ft. from [E] line of sec. 27. C. NE SE 26N 13W New Mexico PM (Meridian) Bisti-Gahlup San Juan New Mexico New Mexico Fish) The elevation of the Works Rock Above sea level is 6198 ft. Ground Level DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding; jobs comentation log from 5012' to 4700', Perforated with 4 super csg. jets per ft. correlation log from 5012' to 4700', Perforated with 4 super csg. jets per ft. correlation with 15 bbls oil at rate of 45 bbls per min. 2800 psi to 2400 psi raced down 5½" csg with 60,000 lbs. sd., 30,000 gals. of lease crude, and 1500 lf Adomite. Frac pressure 2300 psi to 2150 psi at rate of 43.4 bbls per min. lushed with 130 bbls of oil at 2300 psi at rate of 44 bbls per min. Firmal pressure 300 psi. Five min, shut in pressure 1000 psi. Used 980 bbls of load oil. Flow ack 61 bbls. of load oil in 2 hours. Cleaned out 12' of sd. Swabbed 919 bbls coad oil in 4 days. Ran 158 Joints of 2" EUE tubing 4970' and landed at 4980' KB perforated nipple 4945' to 4948'. Pump seating nipple at 4944'. Ran 2" x 1½" x 1mp, 198-3/4" x 25' rods, 4' pony rod, and 1½" x 16' polish rod. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company The British-American Oil Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan	1	
Douthit Well No. B-19 is located 1980. ft. from S line and660. ft. from E line of sec. 27. C. NE. SE 26N 12W New Mexico PM (Grange) (Mendian) Bisti-Gallup San Juan New Mexico Fisch (Field) San Juan New Mexico DETAILS OF WORK (State names of and expected depths to objective anada; show sizes, weights, and lengths of proposed casings; indicate mudding jobs camenting points, and all other important proposed work) BD - 5011' KB - Swabbed hole down and cleaned out to 5011' KB. Ran gamma ray correlation log from 5012' to 4700!, Perforated with 4 super cag. jets per ft. rom 4944' to 4957'. Cleaned out with bailer to 5011'. Loaded hole with 120 bbl il - Breakdown with 15 bbls oil at rate of 45 bbls per min. 2800 psi to 2400 psi raced down 5½" csg with 60,000 lbs. sd., 30,000 gals. of lease crude, and 1500 1f Adomite. Frac pressure 2300 psi to 2150 psi at rate of 43.4 bbls per min. lushed with 130 bbls of oil at 2300 psi at rate of 44 bbls per min. Final press 300 psi. Five min. shut in pressure 1000 psi. Used 980 bbls of load oil. Flowack 61 bbls. of load oil in 2 hours. Cleaned out 12' of sd. Swabbed 919 bbls of act oil in 4 days. Ran 158 joints of 2" EUE tubing 4970' and landed at 4980' KB errorated nipple 4945' to 4948'. Pump seating nipple at 4944'. Ran 2" x 1½" x 12mp, 198-3/4" x 25' rods, 4' pony rod, and 1½" x 16' polish rod. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company The British-American 0il Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan	(INDICATE ABOVE BY CHECK MARI	K NATURE OF REPORT, NOTICE, OR OTHER DATA)
Douthit Well No. B-19 is located 1980. ft. from S line and660. ft. from E line of sec. 27. C. NE. SE 26N 12W New Mexico PM (Grange) (Mendian) Bisti-Gallup San Juan New Mexico Fisch (Field) San Juan New Mexico DETAILS OF WORK (State names of and expected depths to objective anada; show sizes, weights, and lengths of proposed casings; indicate mudding jobs camenting points, and all other important proposed work) BD - 5011' KB - Swabbed hole down and cleaned out to 5011' KB. Ran gamma ray correlation log from 5012' to 4700!, Perforated with 4 super cag. jets per ft. rom 4944' to 4957'. Cleaned out with bailer to 5011'. Loaded hole with 120 bbl il - Breakdown with 15 bbls oil at rate of 45 bbls per min. 2800 psi to 2400 psi raced down 5½" csg with 60,000 lbs. sd., 30,000 gals. of lease crude, and 1500 1f Adomite. Frac pressure 2300 psi to 2150 psi at rate of 43.4 bbls per min. lushed with 130 bbls of oil at 2300 psi at rate of 44 bbls per min. Final press 300 psi. Five min. shut in pressure 1000 psi. Used 980 bbls of load oil. Flowack 61 bbls. of load oil in 2 hours. Cleaned out 12' of sd. Swabbed 919 bbls of act oil in 4 days. Ran 158 joints of 2" EUE tubing 4970' and landed at 4980' KB errorated nipple 4945' to 4948'. Pump seating nipple at 4944'. Ran 2" x 1½" x 12mp, 198-3/4" x 25' rods, 4' pony rod, and 1½" x 16' polish rod. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company The British-American 0il Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan		June 16 19 59
Well No. B-19 is located 1980 ft. from S line and 660 ft. from W line of sec 27 C NE SE (& Sec. and Sec. No.) (Twp.) (Rune) Bisti-Gallup San Juan New Mexico County or Subdivision) The elevation of the **Example And Level** DETAILS OF WORK (State names of and expected depths to objective sands; show size, weights, and lengths of proposed casings; indicate mudding; observed to report and expected depths to objective sands; show size, weights, and lengths of proposed casings; indicate mudding; observed to report and expected depths to objective sands; show size, weights, and lengths of proposed casings; indicate mudding; observed to perform 10g from 5012' to 4700', Perforated with 4 super csg. jets per ft. room 4944' to 4957'. Cleaned out with bailer to 5011'. Loaded hole with 120 bbl i1 - Breakdown with 15 bbls oil at rate of 45 bbls per min. 2800 psi to 2400 psi raced down 5½" csg with 60,000 lbs. sd., 30,000 gals. of lease crude, and 1500 lf Adomite. Frac pressure 2300 psi to 2150 psi at rate of 43.4 bbls per min. Finel press 300 psi. Five min. shut in pressure 1000 psi. Used 980 bbls of load oil. Flow ack 61 bbls. of load oil in 2 hours. Cleaned out 12' of sd. Swabbed 919 bbls of coad oil in 4 days. Ran 158 joints of 2" EUE tubing 4970' and landed at 4980' KB perforated nipple 4945' to 4948'. Pump seating nipple at 4944'. Ran 2" x 1½" x 12mp, 198-3/4" x 25' rods, 4' pony rod, and 1½" x 16' polish rod. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company The British-American Oil Producing Company. Address P. O. Box 180 Original Signed By: Thomas M. Hogan	Douthit	
The elevation of the **Month flow** San Juan New Mexico** (State of Territory) 2 3 1250 (County or Subdivision) The elevation of the **Month flow** San Juan New Mexico** (State of Territory) 2 3 1250 (County of Subdivision) DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding; obs.; comenting of the sands; show sizes, weights, and lengths of proposed casings; indicate mudding; obs.; comenting of the sands; show sizes, weights, and lengths of proposed casings; indicate mudding; obs.; comenting of the sands; show sizes, weights, and lengths of proposed casings; indicate mudding; obs.; comenting of the sands; show sizes, weights, and lengths of proposed casings; indicate mudding; obs.; comenting of the sands of the super case. The sands are said to super case, indicate mudding; obs.; comenting of the super case, indicate mudding; obs.; coment. Company The British-American Oil Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan	Well No. B-19 is located 1980 ft. from	$\begin{bmatrix} \mathbf{A} \\ \mathbf{S} \end{bmatrix}$ line and 660 ft. from $\begin{bmatrix} \mathbf{E} \\ \mathbf{W} \end{bmatrix}$ line of sec. 27
The elevation of the **Month flow** San Juan New Mexico** (State of Territory) 2 3 1250 (County or Subdivision) The elevation of the **Month flow** San Juan New Mexico** (State of Territory) 2 3 1250 (County of Subdivision) DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding; obs.; comenting of the sands; show sizes, weights, and lengths of proposed casings; indicate mudding; obs.; comenting of the sands; show sizes, weights, and lengths of proposed casings; indicate mudding; obs.; comenting of the sands; show sizes, weights, and lengths of proposed casings; indicate mudding; obs.; comenting of the sands; show sizes, weights, and lengths of proposed casings; indicate mudding; obs.; comenting of the sands of the super case. The sands are said to super case, indicate mudding; obs.; comenting of the super case, indicate mudding; obs.; coment. Company The British-American Oil Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan	C NE SE 26N (1/4 Sec. and Sec. No.) (Twp.)	13W New Mexico PM (Range) (Meridian)
The elevation of the day of flood above sea level is 6198 ft. Ground Level DETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding; jobs, comenting points, and all other important proposed work) ED - 5011' KB - Swabbed hole down and cleaned out to 5011' KB. Ran gamma ray correlation log from 5012' to 4700!, Perforated with 4 super csg. jets per ft. rom 4944' to 4957'. Cleaned out with bailer to 5011'. Loaded hole with 120 bbl in a Breakdown with 15 bbls oil at rate of 45 bbls per min. 2800 psi to 2400 psi raced down 5½" csg with 60,000 lbs. sd., 30,000 gals. of lease crude, and 1500 lf Adomite. Frac pressure 2300 psi to 2150 psi at rate of 43.4 bbls per min. It is hold with 130 bbls of oil at 2300 psi at rate of 44 bbls per min. Final press 300 psi. Five min. shut in pressure 1000 psi. Used 980 bbls of load oil. Flow ack 61 bbls. of load oil in 2 hours. Cleaned out 12' of sd. Swabbed 919 bbls of coad oil in 4 days. Ran 158 joints of 2" EUE tubing 4970' and landed at 4980' KB arforated nipple 4945' to 4948'. Pump seating nipple at 4944'. Ran 2" x 1½" x 12mp, 198-3/4" x 25' rods, 4' pony rod, and 1½" x 16' polish rod. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company The British-American Oil Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan		New Mexico
OETAILS OF WORK (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate midding; observed and all other important proposed work) BD - 5011' KB - Swabbed hole down and cleaned out to 5011' KB. Ran gamma ray correlation log from 5012' to 4700!, Perforated with 4 super csg. jets per ft. rom 4944' to 4957'. Cleaned out with bailer to 5011'. Loaded hole with 120 bbl il - Breakdown with 15 bbls oil at rate of 45 bbls per min. 2800 psi to 2400 psi raced down $5\frac{1}{2}$ " csg with 60,000 lbs. sd., 30,000 gals. of lease crude, and 1500 lf Adomite. Frac pressure 2300 psi to 2150 psi at rate of 43.4 bbls per min. lushed with 130 bbls of oil at 2300 psi at rate of 44 bbls per min. Fimal press 300 psi. Five min. shut in pressure 1000 psi. Used 980 bbls of load oil. Flow ack 61 bbls. of load oil in 2 hours. Cleaned out 12' of sd. Swabbed 919 bbls of oad oil in 4 days. Ran 158 joints of 2" EUE tubing 4970' and landed at 4980' KB perforated nipple 4945' to 4948'. Pump seating nipple at 4944'. Ran 2" x 1½" x 12 cmp, 198-3/4" x 25' rods, 4' pony rod, and 1½" x 16' polish rod. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company The British-American Oil Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan		
(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding, jobs, cementing points, and all other important proposed work) BD - 5011' KB - Swabbed hole down and cleaned out to 5011' KB. Ran gamma ray correlation log from 5012' to 4700!, Perforated with 4 super csg. jets per ft. rom 4944' to 4957'. Cleaned out with bailer to 5011'. Loaded hole with 120 bbl il - Breakdown with 15 bbls oil at rate of 45 bbls per min. 2800 psi to 2400 psi raced down 5½" csg with 60,000 lbs. sd., 30,000 gals. of lease crude, and 1500 lf Adomite. Frac pressure 2300 psi to 2150 psi at rate of 43.4 bbls per min. lushed with 130 bbls of oil at 2300 psi at rate of 44 bbls per min. Final press 300 psi. Five min. shut in pressure 1000 psi. Used 980 bbls of load oil. Flow ack 61 bbls. of load oil in 2 hours. Cleaned out 12' of sd. Swabbed 919 bbls of ack 61 bbls. of load oil in 2 hours. Cleaned out 19' of sd. Swabbed 919 bbls of parforated nipple 4945' to 4948'. Pump seating nipple at 4944'. Ran 2" x 1½" x 12" x 13" x 14" x 16' polish rod. Company The British-American 0il Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan	The elevation of the derick Hoar above sea le Ground Level	vel is 0198 ft.
BD - 5011' KB - Swabbed hole down and cleaned out to 5011' KB. Ran gamma ray orrelation log from 5012' to 4700!, Perforated with 4 super csg. jets per ft. rom 4944' to 4957'. Cleaned out with bailer to 5011'. Loaded hole with 120 bbl ii - Breakdown with 15 bbls oil at rate of 45 bbls per min. 2800 psi to 2400 psi raced down 5½" csg with 60,000 lbs. sd., 30,000 gals. of lease crude, and 1500 lf Adomite. Frac pressure 2300 psi to 2150 psi at rate of 43.4 bbls per min. hushed with 130 bbls of oil at 2300 psi at rate of 44 bbls per min. Finel press 300 psi. Five min. shut in pressure 1000 psi. Used 980 bbls of load oil. Flow ack 61 bbls. of load oil in 2 hours. Cleaned out 12' of sd. Swabbed 919 bbls of oil in 4 days. Ran 158 joints of 2" EUE tubing 4970' and landed at 4980' KB erforated nipple 4945' to 4948'. Pump seating nipple at 4944'. Ran 2" x 1½" x 1mp, 198-3/4" x 25' rods, 4' pony rod, and 1½" x 16' polish rod. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company The British-American Oil Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan		.25 01 1/01/11
orrelation log from 5012' to 4700!, Perforated with 4 super csg. jets per ft. rom 4944' to 4957'. Cleaned out with bailer to 5011'. Loaded hole with 120 bbl il - Breakdown with 15 bbls oil at rate of 45 bbls per min. 2800 psi to 2400 psi raced down 5½" csg with 60,000 lbs. sd., 30,000 gals. of lease crude, and 1500 l f Adomite. Frac pressure 2300 psi to 2150 psi at rate of 43.4 bbls per min. lushed with 130 bbls of oil at 2300 psi at rate of 44 bbls per min. Firmal press 300 psi. Five min. shut in pressure 1000 psi. Used 980 bbls of load oil. Flow ack 61 bbls. of load oil in 2 hours. Cleaned out 12' of sd. Swabbed 919 bbls of bad oil in 4 days. Ran 158 joints of 2" EUE tubing 4970' and landed at 4980' KB berforated nipple 4945' to 4948'. Pump seating nipple at 4944'. Ran 2" x 1½" x amp, 198-3/4" x 25' rods, 4' pony rod, and 1½" x 16' polish rod. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company The British-American Oil Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan	State names of and expected depths to objective sands; show siz ing points, and all d	res, weights, and lengths of proposed casings; indicate mudding, jobs; cement- other important proposed work)
Company The British-American Oil Producing Company Address P. O. Box 180 Original Signed By: Thomas M. Hogan	rrelation log from 5012' to 4700!, Pe om 4944' to 4957'. Cleaned out with 1 - Breakdown with 15 bbls oil at raced down $5\frac{1}{2}$ " csg with 60,000 lbs. s Adomite. Frac pressure 2300 psi to ushed with 130 bbls of oil at 2300 p 00 psi. Five min. shut in pressure ck 61 bbls. of load oil in 2 hours. ad oil in 4 days. Ran 158 joints of rforated nipple 4945' to 4948'. Pum	erforated with 4 super csg. jets per ft. n bailer to 5011'. Loaded hole with 120 bbla ate of 45 bbls per min. 2800 psi to 2400 psi ad., 30,000 gals. of lease crude, and 1500 lb b 2150 psi at rate of 43.4 bbls per min. bsi at rate of 44 bbls per min. Final press 1000 psi. Used 980 bbls of load oil. Flowe Cleaned out 12' of sd. Swabbed 919 bbls of 2" EUE tubing 4970' and landed at 4980' KB mp seating nipple at 4944'. Ran 2" x 15" x
Address P. O. Box 180 Original Signed By: Thomas M. Hogan	I understand that this plan of work must receive approval in	writing by the Geological Survey before operations may be commenced.
Thomas M. Hogan	Company The British-American Oil P	roducing Company
	Address P. O. Box 180	Original Signed By:
,	Denver 1. Colorado	