

#6 30-045-09555
#10 30-045-09547

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit A Sec. 18 Twp 30 Rng 10

Name of Well/Wells or Pipeline Serviced _____

SCHUMACHER #6 AND #10

Elevation 6320' Completion Date 2/14/95 Total Depth 432' Land Type F

Casing Strings, Sizes, Types & Depths 2 1/3 SET 98' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented
WITH 20 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT FRESH WATER AT 125'. A WATER SAMPLE
WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 432' DEPTH.
USED 55 SACKS OF LORESCOSW (5500#)

Depths anodes placed: 395', 385', 375', 367', 350', 325', 315', 305', 295', 285', 215', 205', 195', 148', + 140'.

Depths vent pipes placed: SURFACE TO 432'.

Vent pipe perforations: BOTTOM 300'.

Remarks: _____

RECEIVED
JAN 11 1995

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.