

3706

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Co. Location: Unit A Sec. 13 Twp 27 Rng 10

Name of Well/Wells or Pipeline Serviced 30-045-06588

KNAUTH #1

Elevation 6142 Completion Date 2-21-93 Total Depth 417 Land Type F

Casing Strings, Sizes, Types & Depths 2 1/2" SET 97' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used CEMENTED

WITH 22 SACKS

If Cement or Bentonite Plugs have been placed, show depths & amounts used

YES 45' FROM TOP OF COKE-UP

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. 150' - Fresh

Depths gas encountered: Small amount of gas detected around 140' to 160'

Ground bed depth with type & amount of coke breeze used: 417'

SUN LARSEN COKE - 60 BAGS

Depths anodes placed: 400', 390', 380', 370', 360', 350', 340', 330', 320', 310', 300', 290', 280', 270', 260', 250', 240', 230', 220', 210'

Depths vent pipes placed: From Surface to 417'

Vent pipe perforations: Perforated From 150' to 417'

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV.

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.