

30-645-10611

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator LADD PETROLEUM CORPORATION Location: Unit A Sec. 23 Twp. 31N Rng. 13W

Name of Well/Wells or Pipeline Serviced BARKER DOME 1"

Elevation _____ Completion Date 11-29-87 Total Depth 285' Land Type* _____

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. FIRST WATER AT 40', STRINGER

Depths gas encountered: NONE

Type & amount of coke breeze used: 99.9% CARBON, CARBO 60 = 812.5#

Depths anodes placed: 5 170' TO 210'

Depths vent pipes placed: 0' TO 285'

Vent pipe perforations: 160' TO 285'

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED
FEB 04 1991
OIL CON. DIV.
DIST. 3

