

30-045-24400

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator KADD PETROLEUM CORPORATION Location: Unit N Sec. 18 Twp. 27N Rng. 10 W

Name of Well/Wells or Pipeline Serviced ARGO 1E

Elevation _____ Completion Date 11-30-87 Total Depth 250' Land Type*

Casing, Sizes, Types & Depths 8" PVC 0' TO 37'

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NONE

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. FIRST WATER AT 40', STRINGER

Depths gas encountered: NONE

Type & amount of coke breeze used: 99.9% CARBON, CARBO 60 = 1370#

Depths anodes placed: 5 220' TO 250'

Depths vent pipes placed: 0' TO 280'

Vent pipe perforations: 110' TO 280'

Remarks: _____

RECEIVED
FEB 04 1991
OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

GENERAL
CATHODIC PROTECTION SERVICES
WELL TYPE GROUNDBED DATA

DATA SHEET NO. _____

COMPANY LAAD PAPER CORP PIPELINE: _____ JOB No: 13123 DATE: 11-30-87
 WELL: ARGO #1E

LOCATION: SEC 18 TWP. 27N ROR. 10W CO. SNY SPON STATE NM
 ELEV. _____ FT: ROTARY 280' FT: CABLE TOOL _____ FT: CASING 37' FT.
 GROUNDBED: DEPTH 280' FT. DIA. 6 1/4 IN. CAB 1370 LBS. ANODES 5 LAOD STRAIN

DEPTH, FT.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE		NO COKE	WITH COKE	DEPTH OF ANODES	TOP FT.
		E	R				
100	FIRST WITH RE HT 40'						
5	SPALL	0.8		1	1		
10		0.8					
15		0.8					
20		0.6					
25		0.8					
30		0.6					
35		0.6					
40		0.6					
45		0.5					
50		0.4					
55		0.8					
60		1.6					
65		1.1					
70		1.0					
75		0.8					
80	SPALL	0.8					
85		0.7					
90		0.8					
200		0.8					
200		0.9					
5		0.7					
10		0.6					
15	SPALL STRAIN	1.5					
20		1.7				4	220
25		1.7					
30		1.6				3	
35		1.7		4.9	16.9		
40		1.7				2	
45		1.8					
50		1.6				1	250
55		1.2					
60		1.3					
65	SPALL	0.9					
70		1.2					
75		0.9					
80		0.6					
85		0.6					
90							

GROUNDBED RESISTANCE, (1) VOLTS 12.12 AMPS 10.9 OHMS
 (2) VIRROGROUND _____ OHMS