

30-045-28301

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator Bonneville Fuels Corp. Location: Unit NW Sec. 25 Twp 27 Rng 11
Name of Well/Wells or Pipeline Serviced Scott "E" Federal #25-22

Elevation 6249' Completion Date 5/22/91 Total Depth 300' Land Type* F
Casing, Sizes, Types & Depths 8" ID - 8 7/8" dia. O.P. PVC Casing
From 0 to 60 Ft. Deep.

If Casing is cemented, show amounts & types used NA - None

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NA - None

RECEIVED
JUN 7 1991

OIL CON. DIV.

DIST. 3

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. First & Only water (clear)
streak at 110' Deep.

Depths gas encountered: NA - None

Type & amount of coke breeze used: Loresco SN - 99.9% Carbon = 1500 LBS.

Depths anodes placed: 205', 215', 225', 235', 245' + 255' Deep.

Depths vent pipes placed: 0' to 300' Deep, 0' to 100' Deep = Solid 1" dia. PVC.

Vent pipe perforations: Laser Cut Slots From 100' to 300' Deep

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

(1850 FNL & 1695 FNL) DATA SHEET NO. One (1)

COMPANY BONNEVILLE FUELS CORP. JOB No 751-00118 DATE: 5/22/91
WELL: SCOTT "E" FEDERAL #25-22 PIPELINE: _____
LOCATION: SEC. 25 TWP. 27N RGE. 11W CO. SMAN JUAN STATE NM
ELEV. 6249 FT. ROTARY 300 FT. CABLE TOOL _____ FT. CASING 60 FT.
GROUNDBED: DEPTH 300 FT. DIA. 6 IN. GAS 1500 LBS. ANCHORS LIDA STRING

DEPTH, FT.	DRILLER'S LOG		EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	ANODE NO.	DEPTH, TOP OF ANODES
			E	I	R	I	I		
	FIRST WATER 110'								
150	0-60	SAND		5.4					
155	60-140	SAND & SHALE		5.8					
160	140-270	SHALE		5.8					
165	270-300	SAND & SHALE		6.0					
170				5.8					
175				5.7					
180				5.6					
185				5.4					
190				5.5					
195				5.6					
200				5.7					
205				5.8					205
210				5.7					
215				5.8					
220				5.7					
225				5.7					
230				5.7					
235				5.7					
240				5.8					
245				5.7					
250				5.8					
255				5.8			5.8		255
260				5.5					
265				5.1					
270				4.7					
275				3.9					
280				3.8					
285				4.0					
290				4.1					
295				4.5					
300				4.4					
	* LAZER CUT VENT		100'-300'						
	SOLID 1" VENT		0'-100'						

GROUNDING RESISTANCE: (1) VOLTS 12.25 - AMPS 23.5 - .52 OHMS

(2) VIBROGROUND _____ CHMS

GENERAL CATHODIC PROTECTION SERVICES CO.

A LUXURY COMPANY