Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103	
District I	Energy, Minerals and Natural Re	esources	May 27, 2004	
1625 N French Dr, Hobbs, NM 88240 District II		WELL A 30-045-34		
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIV	ISION 5 Indica:	te Type of Lease	
District III 1000 Rio Brazos Rd, Aztec, NM 87410	1220 South St. Francis D	Or. ST	ATE FEE	
District IV	Santa Fe, NM 87505		Oil & Gas Lease No.	
1220 S St Francis Dr , Santa Fe, NM 87505		V-2364		
•	ICES AND REPORTS ON WELLS		Name or Unit Agreement Name	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			Road Runner	
PROPOSALS.)		Road Ru	8. Well Number	
1. Type of Well: Oil Well Gas Well Other		92		
2. Name of Operator			D Number	
Dugan Production Corp.		006515	Will	
3. Address of Operator P. O. Box 420, Farmington, NM 87499-0420		l l	10. Pool name or Wildcat Basin Fruitland Coal	
4. Well Location	7777-0420	Dasiii i u	Ittalia Coal	
Unit Letter B : 1200 feet from the North line and 1850 feet from the East line				
Section 36 Township 24N Range 11W NMPM San Juan County				
11. Elevation (Show whether DR, RKB, RT, GR, etc.)				
6511'GL				
Pit or Below-grade Tank Application □ or Closure □				
Pit typeDepth to GroundwaterDistance from nearest fresh water well Distance from nearest surface water				
Pit Liner Thickness: mil	Below-Grade Tank: Volume	bbls; Construction M	aterial	
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data				
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING				
TEMPORARILY ABANDON				
PULL OR ALTER CASING	= 1	ING/CEMENT JOB		
OTHER ALIV LARRY		uen.	-	
OTHER: Additional APD information				
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion				
or recompletion.				
Blow-out Preventor Equipment (BOPE) tests will be performed without using a test plug.				
Blow out Troventor Equipment (Box B) tests will be personned minious using a test plug.				
Will test the BOPE and surface casing together. The test will include a low pressure test to 250 psig held for five minutes				
and a high pressure test to 800 psig held for thirty minutes (with no more than a 10 percent pressure drop during the duration of the tests). If a 10 percent or greater pressure drop occurs, a packer will be run to isolate the surface casing				
and BOPE to locate the source of the leak.				
and Sol 2 to locate the sol	ace of the real.			
			graphs are assess to enter-	
			RCVD MAY 9 '08	
			OIL CONS. DIV.	
			DIST. 3	
I hereby certify that the information	above is true and complete to the best of i	ny knowledge and belief	. I further certify that any pit or below-	
grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square .				
SIGNATURE KAST FOR	TITLE VI	Danidant Familiantian	DATE 5 (00	
SIGNATURE // W/ T2g/	IIILE Vice-	President, Exploration	DATE <u>5-6-08</u>	
Type or print name Kurt Fagrelius E-mail address: kfagrelius@duganproduction.com Telephone No. 505-325-1821				
For State Use Only		<u> </u>		
APPROVED BY: H. Vill	Deputy	Oil & Gas Inspect District #3	DATE MAY 1 3 2008	
Conditions of Approval (if any):	Deputy TITLE A	Diomor " o	DATE	
	<i>(</i> 1)			