

662

E

30-039-24983

DATA SHEET FOR DEEP GROUND-BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

22914

Operator MERIDIAN Oil INC. Location: Unit G Sec. 22 Twp 31 Rng 5

Name of Well/Wells or Pipeline Serviced ROSA UNIT # 264

Elevation 6609 Completion Date 9-26-91 Total Depth 482' Land Type SF 078770

Casing Strings, Sizes, Types & Depths 60' 8" PVC SURFACE CASING

If Casing Strings are cemented, show amounts & types used 12 SACKS

CLEAN CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used

Depths & thickness of water zones with description of water: Fresh Clear,
Salty, Sulphur, Etc. MOIST SANDSTONE APPROX. 70'

RECEIVED

FEB 24 1992

Depths gas encountered: _____

OIL CON. DIV. J
DIST. 3

Ground bed depth with type & amount of coke breeze used: 482' loaded
w/163 SACKS Ashbury 4518 FLOCOKE

Depths anodes placed: 445; 415; 395; 370; 355; 315; 300; 285; 255; 190; 160; 145

Depths vent pipes placed: 415' 1" PVC VENT PIPE

Vent pipe perforations: BOTTOM 360'

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

2297W

Operator MERIDIAN OIL INC. Location: Unit A Sec. 23 Twp 31 Rng 5

Name of Well/Wells or Pipeline Serviced ROSA UNIT # 322

Elevation 6571 Completion Date 9-28-91 Total Depth 483 Land Type SF 078770

Casing Strings, Sizes, Types & Depths 60' 8" PVC SURFACE CASING

If Casing Strings are cemented, show amounts & types used 17 SACKS

CLEAN CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. MOISTURE APPROX. 140' to 150'

Depths gas encountered: _____

Ground bed depth with type & amount of coke breeze used: 483 ²⁰⁸ 163 SACKS

Asbury A510 F10 COKE

Depths anodes placed: 450, 425, 395, 340, 325, 285, 265, 245, 220, 185, 160, 135

Depths vent pipes placed: 425

Vent pipe perforations: BOTTOM 360'

RECEIVED

FEB 24 1992

Remarks: _____

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2297	P/L NAME (S), NUMBER (S) ROSA UNIT #322					
WO # L922	TOTAL	VOLTS 11.8	AMPS 324	OHMS .36	DATE 9-28-91	NAME W.R. McCATA
REMARKS (notes for construction log) Set 100' 8" PVC surface casing cemented w/12 sacks, No H ₂ O; moisture approx. 140. Install 425' 1" PVC & perf. bottom 360'. Log 478'; Total Depth 483. Load w/208 sacks of Ashmug 4518 Flo-Coke.						

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	NO COKE	FULLY COK'D
100	4.5		295	3.1		490			685							
105	4.2		300	3.1		495			690							
110	4.7		305	3.1		500			695							
115	4.9		310	3.8		505			700							
120	4.9		315	3.9		510				ANODE	DEPTH					
125	5.3		320	4.0		515				*						
130	5.3		325	4.1	5✓	520			1	450	4.0	6.9				
135	5.3	12✓	330	3.8		525			2	425	3.6	6.4				
140	4.6		335	4.1		530			3	395	4.4	6.7				
145	3.5		340	4.0	4✓	535			4	340	4.1	5.8				
150	4.4		345	3.7	#	540			5	325	4.3	6.3				
155	5.0		350	3.0		545			6	285	4.0	5.8				
160	4.8	11✓	355	2.5		550			7	265	4.4	6.1				
165	4.2		360	2.5		555			8	245	4.6	6.1				
170	4.2		365	2.8		560			9	220	4.3	5.9				
175	3.9		370	3.1		565			10	185	4.4	6.1				
180	4.1		375	3.6		570			11	160	5.3	7.2				
185	4.3	10✓	380	3.2		575			12	135	5.7	7.9				
190	4.1		385	2.6		580			13							
195	4.0		390	3.7		585			14							
200	3.9		395	4.3	3✓	590			15							
205	3.6		400	4.0		595			16							
210	3.0		405	3.3		600			17							
215	3.9		410	3.0		605			18							
220	4.3	7✓	415	3.4		610			19							
225	3.3		420	3.6		615			20							
230	3.2		425	3.6	2✓	620			21							
235	3.3		430	3.6		625			22							
240	3.5		435	3.3		630			23							
245	4.3	8✓	440	3.0		635			24							
250	4.3		445	3.7		640			25							
255	3.7		450	4.0	1✓	645			26							
260	3.7		455	3.3		650			27							
265	4.2	7✓	460	3.3		655			28							
270	3.7		465	3.6		660			29							
275	3.9		470	3.3		665			30							
280	4.0		475	3.2		670										
285	4.0	6✓	480		483	675										
290	3.1		485			680										

DISTRIBUTION - original - permanent CPS FILE
 70' 5.0 90' 4.8 copy - Division Corrosion Supervisor
 75' 5.1 95' 4.7 copy - Region Corrosion Specialist
 80' 5.2
 85' 4.0