## DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO (Submit 3 copies to OCD Aztec Office)

| Operator MERIDIAN OIL Location: UnitSW Sec 24 Twp 29 Rng7                      |
|--|
| Name of Well/Wells or Pipeline Serviced SAN JUAN 29-7 UNIT #73                 |
| cps 318w   |
| Elevation6726' Completion Date6/24/77 Total Depth543' Land Type* N/A           |
| Casing, Sizes, Types & Depths N/A  |
| If Casing is cemented, show amounts & types used N/A                           |
| If Cement or Bentonite Plugs have been placed, show depths & amounts used  N/A |
| Depths & thickness of water zones with description of water when possible:     |
| Fresh, Clear, Salty, Sulphur, Etc. N/A   |
| <u>DECEIVEN</u>  |
| Depths gas encountered: N/A MAY 31 1991  |
| Type & amount of coke breeze used: 71 SACKS OIL CON DIV                        |
| Depths anodes placed: 515', 475', 455', 430', 415'                             |
| Depths vent pipes placed: 520'   |
| Vent pipe perforations: 360'   |
| Remarks: gb #3   |
|  |

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

<sup>\*</sup>Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.



## OIL CON. I

## DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO (Submit 3 copies to OCD Aztec Office)

| Operator MERIDIAN OIL Location: UnitSW Sec.24 Twp 29 Rng 7                          |
|---|
| Name of Well/Wells or Pipeline Serviced SAN JUAN 29-7 UNIT #73                      |
| cps 318w  |
| Elevation 6726' Completion Date 9/11/69 Total Depth 540' Land Type* N/A             |
| Casing, Sizes, Types & Depths N/A   |
| If Casing is cemented, show amounts & types used N/A                                |
| If Cement or Bentonite Plugs have been placed, show depths & amounts used  N/A      |
| Depths & thickness of water zones with description of water when possible:          |
| Fresh, Clear, Salty, Sulphur, Etc. WET SPOTS 140', 360', 410'                       |
| Depths gas encountered: N/A   |
| Type & amount of coke breeze used: 7900 lbs.  |
| Depths anodes placed: 508', 502', 496', 490', 484', 478', 472', 466'                |
| Depths vent pipes placed: 502' OF 3/4" HOSE   |
| Vent pipe perforations: 300'  |
| Remarks: gb #2 PLASTIC MOLD USED TO CAP ANODES. EPOXY POURED ABOVE SHRINK SLEEVE ON |
| WIRE.   |

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

<sup>\*</sup>Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

## DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO (Submit 3 copies to OCD Aztec Office)

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

<sup>\*</sup>Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.